

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

UltraCrete Envirobed CD534 High Performance Mortar - 40x 18kg Buckets

Product Images Product Code: S00-4047





Short Description

The environmentally friendly alternative to resin-based materials, specifically formulated for the bedding of all access covers. Envirobed® CD534 (formerly HA104) has been HAPAS Approved since 2005 and conforms to CD534. Its superior compressive, tensile and flexural strengths make it ideal for use in heavily trafficked / wheel track locations. It can be open to traffic after just 1 hour.

Features

Workability: 15 minutes Set Time: 30 minutes Depth: 10mm -50mm

53N/mm² compressive strength in 3 hours 12N/mm² flexural strength in 3 hours 6.10N/mm² tensile strength in 3 hours

No hazardous waste disposal

Can be used in wet conditions and in temperatures as low as 1°C Approved for use on the London Underground and Overground NBS Source registered for ease of specification UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

40x 18kg bucket (each includes 2 x 8kg bags and 2 x 1l bottles)

Please see datasheet for further details

Description

The environmentally friendly alternative to resin-based materials, specifically formulated for the bedding of all access covers. Envirobed® CD534 (formerly HA104) has been HAPAS Approved since 2005 and conforms to CD534. Its superior compressive, tensile and flexural strengths make it ideal for use in heavily trafficked / wheel track locations. It can be open to traffic after just 1 hour.

Features

Workability: 15 minutes Set Time: 30 minutes Depth: 10mm -50mm

53N/mm² compressive strength in 3 hours 12N/mm² flexural strength in 3 hours 6.10N/mm² tensile strength in 3 hours

No hazardous waste disposal

Can be used in wet conditions and in temperatures as low as 1°C

Approved for use on the London Underground and Overground

NBS Source registered for ease of specification UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

40x 18kg bucket (each includes 2 x 8kg bags and 2 x 1l bottles)

Please see datasheet for further details