

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600

Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

UltraCrete Envirobed CD534 RED High Performance Mortar - 40x 18kg Buckets

Product Images Product Code: S00-4045



Short Description

Envirobed® CD534 Red, (part of UltraCrete's HAPAS Approved Ironwork Reinstatement System), is pigmented red as a prescriptive solution for specific contracts and frame works to easily identify the composition of work carried out. It is supplied as a two-component system, which contains a blend of special cements, polymer and aggregates and recycled glass. The combined components provide a high strength mortar, which can accommodate depths of 10-50mm in one pass. If necessary, greater depths am be achieved by using the layer-upon-layer method.

Features

- HAPAS approved
- Conforms to CD534 (formerly HA104)
- Detectably red
- Can be used in the wet
- BT LN550 and LN320 compliant
- 53N/mm² compressive strength in 3 hours
- 6.10N/mm² tensile strength at 3 hours
- Size: 18kg bucket includes 2 x 8kg bags and 2 x 1l bottles
- NBS Source registered for ease of specification
- UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of: 40x 18kg buckets (inc. 2x 8kg bags and 2x 1 litre bottles)

Please see datasheet for further details

Description

Envirobed® CD534 Red, (part of UltraCrete's HAPAS Approved Ironwork Reinstatement System), is pigmented red as a prescriptive solution for specific contracts and frame works to easily identify the composition of work carried out. It is supplied as a two-component system, which contains a blend of special cements, polymer and aggregates and recycled glass. The combined components provide a high strength mortar, which can accommodate depths of 10-50mm in one pass. If necessary, greater depths am be achieved by using the layer-upon-layer method.

Features

HAPAS approved
Conforms to CD534 (formerly HA104)
Detectably red
Can be used in the wet
BT LN550 and LN320 compliant
53N/mm² compressive strength in 3 hours

6.10N/mm² tensile strength at 3 hours

Size: 18kg bucket includes 2 x 8kg bags and 2 x 1l bottles

NBS Source registered for ease of specification

UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of: 40x 18kg buckets (each inc. 2x 8kg bags and 2x 1 litre bottles)

Please see datasheet for further details