

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

UltraCrete PY4 Winter Grade CD534 Polyester Resin System -30x 25kg Buckets

Product Images

Product Code: S00-4048





PY4 WG **Winter Grade** produces a stiff supporting mortar, and is effective for the rapid installation and reinstatement of manhole covers and frames in heavily trafficked areas. It is highly recommended for ductile ironwork and has been HAPAS approved since 2005. PY4 conforms to HA104/09, has a rapid strength gain and can be opened to traffic in 40 minutes.

Features

Workability: 5 – 10 minutes Set time: 15 minutes Depth: 5mm – 50mm 8.25N/mm² tensile strength in 1 hour 61.5N/mm² compressive strength in 1 hour 19N/mm² flexural strength in 1 hour NBS Source registered for ease of specification UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

30x 25kg buckets

Please see datasheet for further details

Description

PY4 WG **Winter Grade** produces a stiff supporting mortar, and is effective for the rapid installation and reinstatement of manhole covers and frames in heavily trafficked areas. It is highly recommended for ductile ironwork and has been HAPAS approved since 2005. PY4 conforms to HA104/09, has a rapid strength gain and can be opened to traffic in 40 minutes.

<u>Features</u>

Workability: 5 – 10 minutes Set time: 15 minutes Depth: 5mm – 50mm 8.25N/mm² tensile strength in 1 hour 61.5N/mm² compressive strength in 1 hour 19N/mm² flexural strength in 1 hour NBS Source registered for ease of specification UltraCrete Accredited Reinstatement Specification (UCARS) product

Supplied on a pallet of:

30x 25kg buckets

Please see datasheet for further details