

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Megger MIT1525-UK High Voltage DC Insulation Resistance Tester -15kV

Product Images

Product Code: C00-0119



Offering CAT IV safety, the MIT1525 is compact, light 15 kV insulation resistance tester for the diagnostic testing and maintenance of high voltage electrical equipment. It benefits from the Megger dual case construction, Tough on the outside and fire retardant on the inside.

As well as measuring insulation resistance to $30 \text{ T}\Omega$, the MIT1525 also offers various diagnostic tests such as Polarisation index, Dielectric Absorption Ratio, Step Voltage, Dielectric discharge and ramp testing.

Now equipped with lithium ion fast rechargeable batteries, the instrument has a large, clear, easy to read, display making it equally suitable for use in both bright sunlight and poorly lit environments. Information displayed includes resistance, voltage, leakage current, capacitance, battery status and time constant. In addition, the elapsed time of the test is displayed constantly removing the need for separate timer.

Features

- Measures up to $30 \text{ T}\Omega$
- PI, DAR, DD, SV and ramp test
- Improved productivity operate from line power/mains if battery dead
- Li ion battery extended capacity, rapid charge
- Advanced memory with time/date stamp
- CATIV 600 V safety rating

Please see datasheet for further details

Description

Offering CAT IV safety, the MIT1525 is compact, light 15 kV insulation resistance tester for the diagnostic testing and maintenance of high voltage electrical equipment. It benefits from the Megger dual case construction, Tough on the outside and fire retardant on the inside.

As well as measuring insulation resistance to $30 \text{ T}\Omega$, the MIT1525 also offers various diagnostic tests such as Polarisation index, Dielectric Absorption Ratio, Step Voltage, Dielectric discharge and ramp testing.

Now equipped with lithium ion fast rechargeable batteries, the instrument has a large, clear, easy to read, display making it equally suitable for use in both bright sunlight and poorly lit environments. Information displayed includes resistance, voltage, leakage current, capacitance, battery status and time constant. In addition, the elapsed time of the test is displayed constantly removing the need for separate timer.

Features

Measures up to 30 TΩ PI, DAR, DD, SV and ramp test Improved productivity – operate from line power/mains if battery dead Li ion battery - extended capacity, rapid charge Advanced memory with time/date stamp CATIV 600 V safety rating

Please see datasheet for further details