

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Knipex 26 26 200 1000V VDE Bent Snipe Nose Side Cutting Pliers 200mm

Product Images

Product Code: E00-0106



These forged, oil-hardened and insulated stork beak pliers with multi-component grip are ideal for installation, insertion and assembly, as well as powerful cutting. The cutting edges of the pliers are shaped to produce a pierced cut. The Knipex 26 26 200 also cuts hard wires.

Dimensionally stable under torsion - very powerful when cutting

The flexible precision tips made of vanadium electric steel are torsion-resistant and angled 40°. The pliers allow you to control the manual force. The cutting edge position near the joint favours the transmission of force. This results in impressive cutting values for medium-hard wire of up to 3.2 Ømm and for hard wire of up to 2.2 Ømm.

Components and wires are easily accessible in control cabinets, machines or electric motors

Whether connecting wires to conductor terminals, in junction boxes or in control cabinet construction – the extra-long tips of the VDE tested stork beak pliers from Knipex 26 26 200 allow you to work efficiently, especially when space is tight. Their qualities are appreciated whenever cables and wires need to be held, inserted or cut.

- Elastic tips: dimensionally stable even when twisted
- Distortion-tolerant, elastic precision tips
- Half-round, long, tapered jaws
- With cutting edges for soft, medium-hard and hard wire
- Cutting edges additionally induction-hardened, cutting edge hardness approx. 61 HRC
- 40° angled jaws
- Vanadium electric steel, forged, multi stage oil-hardened

Specification

Head chrome-plated Handles insulated with multi-component grips, VDE-tested Weight 204 g Dimensions 200 x 56 x 19 mm Standard DIN ISO 5745 DIN EN 60900 IEC 60900 Cutting capacities medium hard wire (diameter) Ø 3.2 mm Cutting capacities hard wire (diameter) Ø 2.2 mm Jaw thickness (joint) (T1) 9.5 mm Tips width (W4) 3.0 mm Tips thickness (T2) 2.5 mm Gripping surface length (L4) 23.0 mm Jaw length (L3) 73.0 mm Head width (W3) 18 mm

Description

These forged, oil-hardened and insulated stork beak pliers with multi-component grip are ideal for installation, insertion and assembly, as well as powerful cutting. The cutting edges of the pliers are shaped to produce a pierced cut. The Knipex 26 26 200 also cuts hard wires.

Dimensionally stable under torsion - very powerful when cutting

The flexible precision tips made of vanadium electric steel are torsion-resistant and angled 40°. The pliers allow you to control the manual force. The cutting edge position near the joint favours the transmission of force. This results in impressive cutting values for medium-hard wire of up to 3.2 Ømm and for hard wire of up to 2.2 Ømm.

Components and wires are easily accessible in control cabinets, machines or electric motors

Whether connecting wires to conductor terminals, in junction boxes or in control cabinet construction – the extra-long tips of the VDE tested stork beak pliers from Knipex 26 26 200 allow you to work efficiently, especially when space is tight. Their qualities are appreciated whenever cables and wires need to be held, inserted or cut.

<u>Features</u>

Elastic tips: dimensionally stable even when twisted Distortion-tolerant, elastic precision tips Half-round, long, tapered jaws With cutting edges for soft, medium-hard and hard wire Cutting edges additionally induction-hardened, cutting edge hardness approx. 61 HRC 40° angled jaws Vanadium electric steel, forged, multi stage oil-hardened

Specification

Head chrome-plated Handles insulated with multi-component grips, VDE-tested Weight 204 g Dimensions 200 x 56 x 19 mm Standard DIN ISO 5745 DIN EN 60900 IEC 60900 Cutting capacities medium hard wire (diameter) Ø 3.2 mm Cutting capacities hard wire (diameter) Ø 2.2 mm Jaw thickness (joint) (T1) 9.5 mm Tips width (W4) 3.0 mm Tips thickness (T2) 2.5 mm Gripping surface length (L4) 23.0 mm Jaw length (L3) 73.0 mm Head width (W3) 18 mm