


# Drager Saver CF15 - 15 Minute Emergency Escape Breathing Apparatus (Soft Case)

## Product Images

Product Code: S26-1090



## Short Description

CF15 escape set for protection in a hazardous environment where smoke or toxic fumes may be present.

The CF emergency escape device uses an escape hood with positive pressure which provides a continuous supply of breathing air for 15 minutes.

Housed in a bright soft bag the Dräger CF15 is light and comfortable to carry which is ideal for escaping from an emergency situation. The material used for the bag is highly resistant to flames and can be easily washed and drained. The bag also features a transparent window which allows the pressure gauge on the cylinder to be view without taking it out of the bag.

This Dräger escape set requires very little maintenance over its lifetime and also requires minimal training.

### Key Features

Escape hood suitable for those with facial hair or wear glasses

Can be wall mounted with additional accessories

Wear over the shoulder or as a chest bag

Provides a consistent rate of air flow until the cylinder is empty at which point an alarm whistle will sound

### When time is of the essence

In emergency situations, conditions can deteriorate rapidly. The air is suddenly filled with smoke or toxic fumes and rapid escape is the only available option. The Dräger Saver CF is highly visible and was designed to be suitable even for people with spectacles or facial hair. When opened, the Saver CF is automatically activated and begins feeding a continuous supply of breathing air to the hood. The Saver CF gives the wearer the precious additional time needed to exit the area safely.

### Highly visible, even under adverse conditions

The Saver CF can be easily wall-mounted in strategic locations in potentially hazardous areas. The bright orange bags feature photoluminescent panels and reflective stripes for enhanced visibility, even under low lighting conditions. The Saver CF is compact and lightweight and can be worn either as a chest bag or over the shoulder. Made from highly resistant materials, it is washable, flame retardant and allows water to drain freely.

### Up to 15 minutes of lifesaving air

The Dräger Saver CF utilizes a simple, fail-safe reducer system with excellent flow characteristics, providing a consistent rate of air flow until the cylinder is completely empty. An alarm whistle sounds before the air supply is exhausted. It can be equipped with cylinders which can hold either a 10 or 15 minute supply of air. The flame retardant hood incorporates a large visor for maximum peripheral vision.

### Low-maintenance protection

The Dräger Saver CF requires very little service or maintenance. A transparent window on both the soft bag lets you check the cylinder pressure gauge easily without unpacking the unit. You know the Saver CF is there for you when you need it.

### Conforms to relevant standards and norms

The Dräger Saver CF complies with the essential health and safety requirements of the PPE Regulation (EU)

2016/425 and is tested and designed in accordance with EN1146 (2005), DNV GL Certificate of Fire Approval

and DNV GL Certificate of Type Approval. It also complies with SOLAS Chapter II-2, the

## Description

---

CF15 escape set for protection in a hazardous environment where smoke or toxic fumes may be present.

The CF emergency escape device uses an escape hood with positive pressure which provides a continuous supply of breathing air for 15 minutes.

Housed in a bright soft bag the Dräger CF15 is light and comfortable to carry which is ideal for escaping from an emergency situation. The material used for the bag is highly resistant to flames and can be easily washed and drained. The bag also features a transparent window which allows the pressure gauge on the cylinder to be view without taking it out of the bag.

This Dräger escape set requires very little maintenance over its lifetime and also requires minimal training.

### Key Features

Escape hood suitable for those with facial hair or wear glasses

Can be wall mounted with additional accessories

Wear over the shoulder or as a chest bag

Provides a consistent rate of air flow until the cylinder is empty at which point an alarm whistle will sound

### When time is of the essence

In emergency situations, conditions can deteriorate rapidly. The air is suddenly filled with smoke or toxic fumes and rapid escape is the only available option. The Dräger Saver CF is highly visible and was designed to be suitable even for people with spectacles or facial hair. When opened, the Saver CF is automatically activated and begins feeding a continuous supply of breathing air to the hood. The Saver CF gives the wearer the precious additional time needed to exit the area safely.

### Highly visible, even under adverse conditions

The Saver CF can be easily wall-mounted in strategic locations in potentially hazardous areas. The bright orange bags feature photoluminescent panels and reflective stripes for enhanced visibility, even under low lighting conditions. The Saver CF is compact and lightweight and can be worn either as a chest bag or over the shoulder. Made from highly resistant materials, it is washable, flame retardant and allows water to drain freely.

### Up to 15 minutes of lifesaving air

The Dräger Saver CF utilizes a simple, fail-safe reducer system with excellent flow characteristics, providing a consistent rate of air flow until the cylinder is completely empty. An alarm whistle sounds before the air supply is exhausted. It can be equipped with cylinders which can hold either a 10 or 15 minute supply of air. The flame retardant hood incorporates a large visor for maximum peripheral vision.

### Low-maintenance protection

The Dräger Saver CF requires very little service or maintenance. A transparent window on both the soft bag lets you check the cylinder pressure gauge easily without unpacking the unit. You know the Saver CF is there for you when you need it.

#### Conforms to relevant standards and norms

The Dräger Saver CF complies with the essential health and safety requirements of the PPE Regulation (EU)

2016/425 and is tested and designed in accordance with EN1146 (2005), DNV GL Certificate of Fire Approval

and DNV GL Certificate of Type Approval. It also complies with SOLAS Chapter II-2, the Marine Equipment

Directive, the Pressure Equipment Directive and ISO 23269-1:2008.

#### Specifications

Cylinder and charging pressure: 3L 200 bar

Airflow to the hood: 35-37 l/min

Operating Temperature Gauge: -15°C to +60°C

Approvals:

EN1146 (2005)

ISO 23269-1:2008

SOLAS Chapter II-2, the Marine Equipment Directive and the Pressure Equipment Directive

What's Included?

CF15 – cylinder with 15 minute escape supply

Hood

Soft Bag

Anti-Tamper Tags

Dimensions: 510 x 260 x 190 mm

Weight 5.2 kg

**Also available for rent from Sunbelt Rentals.**

