
Telenco DS15 Suspension Clamp for 15-17mm Round ADSS Cable - Box of 30

[Product Images](#)

Product Code: S83-1689



Short Description

Designed to provide suspension for aerial round ADSS cables on drop networks where spans do not exceed 70m.

The suspension clamp consists of a nylon body with a nylon bail and a neoprene sleeve.

The body is secured around the cable with 2 clips and one tie.

All parts are UV protected.

Features

- Monobloc and cost-efficient design.
- Simple, fast and tool-less installation.DS2DS4DS6
- Installation without bending of the optical cable in the device.
- Direct installation on mounting hardware Ø10mm min. eye or pigtail type.

Installation

- When the line is at an angle of less than 15 °.
- When the cable is passing through intermediate poles up to 4 consecutive poles.
- In case of balanced adjacent spans. Installation of a double anchorage in place of a suspension in the following cases:
 - On end poles.
- When the line is at an angle greater than 15° (instead of a suspension device), in order to preserve the integrity of the cable over time.
- If road crossing (obligatory cable stop on each pole both sides of the road).
- In case of unbalanced adjacent spans (a span of 40m, followed by a span of 30m, for example).
- If rugged terrain (line mountainside down for example).
- In alignment every 5 poles

Testing

This clamp has been qualified in accordance with internationally recognised standards :

- Climatic ageing test according to NF EN C-20-540 standard dated June 2002.
- Tensile test according to the technical specification ORANGE CCF/BI/BUBL of 20 May 2010.
- Vibration test according to the technical specification ORANGE CCF/BI/BUBL of 20 May 2010 and the standard NF EN 50289-3-13 of August 2003 with insertion loss < 0.2 dB.

Supplied in a box of 30

Description

Designed to provide suspension for aerial round ADSS cables on drop networks where spans do not exceed 70m.

The suspension clamp consists of a nylon body with a nylon bail and a neoprene sleeve.

The body is secured around the cable with 2 clips and one tie.

2

All parts are UV protected.

Features

- Monobloc and cost-efficient design.
- Simple, fast and tool-less installation.DS2DS4DS6
- Installation without bending of the optical cable in the device.
- Direct installation on mounting hardware Ø10mm min. eye or pigtail type.

Installation

- When the line is at an angle of less than 15 °.
- When the cable is passing through intermediate poles up to 4 consecutive poles.
- In case of balanced adjacent spans. Installation of a double anchorage in place of a suspension in the following cases:
 - On end poles.
 - When the line is at an angle greater than 15° (instead of a suspension device), in order to preserve the integrity of the cable over time.
 - If road crossing (obligatory cable stop on each pole both sides of the road).
 - In case of unbalanced adjacent spans (a span of 40m, followed by a span of 30m, for example).
 - If rugged terrain (line mountainside down for example).
 - In alignment every 5 poles

Testing

This clamp has been qualified in accordance with internationally recognised standards :

- Climatic ageing test according to NF EN C-20-540 standard dated June 2002.
- Tensile test according to the technical specification ORANGE CCF/BI/BUBL of 20 May 2010.
- Vibration test according to the technical specification ORANGE CCF/BI/BUBL of 20 May 2010 and the standard NF EN 50289-3-13 of August 2003 with insertion loss < 0.2 dB.

Supplied in a box of 30