
Gloves - LV Low Voltage 1000V Insulated EN60903 Class 0 - Size 8

Product Images

Product Code: H87-7366/8



Short Description

Ideal for use by Electrical workers who come into contact with live, or potentially live, cables and circuits. The highest quality latex high voltage insulating glove ever produced, using a combination of traditional latex dip and cement dip technologies.

Offering excellent feel and dexterity in use and maximum protection for the wearer.

The glove is tested and marked in accordance with EN60903:2003. It is also marked with CE and the double triangle icon for live working.

Temperature: Resistant to temperatures +55°C to -40°C.

Flame Retardancy: As per requirements of EN 60903.

Packaging: Supplied as a pair contained within a white plastic bag bearing care instructions.

Storage: Gloves should be stored in their packaging. Care should be taken to ensure that gloves are not compressed, folded, or stored in proximity sources of heat or exposed to sources of ozone. It is desirable that the ambient temperature be between 10 and 21°C.

Length: 355mm

Working Voltage: 1000v AC

Test Voltage:5000v AC

Class: 0

Size 8

Formerly S00-7894-8

Description

Ideal for use by Electrical workers who come into contact with live, or potentially live, cables and circuits. The highest quality latex high voltage insulating glove ever produced, using a combination of traditional latex dip and cement dip technologies.

Offering excellent feel and dexterity in use and maximum protection for the wearer.

The glove is tested and marked in accordance with EN60903:2003. It is also marked with CE and the double triangle icon for live working.

Temperature: Resistant to temperatures +55°C to -40°C.

Flame Retardancy: As per requirements of EN 60903.

Packaging: Supplied as a pair contained within a white plastic bag bearing care instructions.

Storage: Gloves should be stored in their packaging. Care should be taken to ensure that gloves are not compressed, folded, or stored in proximity sources of heat or exposed to sources of ozone. It is desirable that the ambient temperature be between 10 and 21°C.

Length: 355mm

Working Voltage: 1000v AC

Test Voltage:5000v AC

Class: 0

Size 8

Formerly S00-7894-8