

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

FatMax Tape 8m /26ft 1 1/4" 9N33726E

Product Images

Product Code: K70-3417















https://www.millsltd.com/default/fatmax-tape-8m-26ft-1-1-4-9n33726e.html 26/04/2024



Short Description

The Stanley FatMax 8M/26ft Tape Measure with 32mm blade width for clear and legible markings, is class II accurate providing a reassuring +/- 0.5mm error tolerance at 1m, suitable for the majority of professionals. Its abrasion resistant polyester film coated blade coating provides up to 10 times more resistance to abrasion than a standard lacquered blade, with additional BladeArmor® coating, reinforcing the first 7.5cm of the blade, the section most vulnerable to wear, and its TRU-ZERO[™] hook provides for precise inner and outer measurements, moving back and forth along the securing rivets to account for the hook thickness. Complete with a multi-catch hook to catch onto building materials with ease above, below and to either side, making for hassle-free regular measurements, side measurements and even overhead measurement.

Description

The Stanley FatMax 8M/26ft Tape Measure with 32mm blade width for clear and legible markings, is class II accurate providing a reassuring +/- 0.5mm error tolerance at 1m, suitable for the majority of professionals. Its abrasion resistant polyester film coated blade coating provides up to 10 times more resistance to abrasion than a standard lacquered blade, with additional BladeArmor® coating, reinforcing the first 7.5cm of the blade, the section most vulnerable to wear, and its TRU-ZERO[™] hook provides for precise inner and outer measurements, moving back and forth along the securing rivets to account for the hook thickness. Complete with a multi-catch hook to catch onto building materials with ease above, below and to either side, making for hassle-free regular measurements, side measurements and even overhead measurement.

Additional Features

• TRU-ZERO[™] HOOK for precise inner and outer measurements, moving back and forth along the https://www.millsltd.com/default/fatmax-tape-8m-26ft-1-1-4-9n33726e.html 26/04/2024 securing rivets to account for the hook thickness and

- MULTI-CATCH HOOK provides more contact surface and grip for greater control, while the TRU-ZERO[™] feature ensures precise inner and outer measurements.
- PORTABILITY: Can be easily secured to a belt, pocket, or waistband using the integral belt clip.
- CLASS II ACCURACY suitable for most professionals, providing a reassuring +/-0,5mm error tolerance at 1m.