

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Knipex Linesman's Combination Plier 240mm with Tethering Loop

Product Images Product Code: E70-1455



Short Description

Handles with slim multi-component grips, with integrated tether attachment point for a tool tether.

- High transmission ratio for easy cutting
- Requires 50 % less effort compared with conventional combination pliers thanks to optimised transmission ratio
- With fish tape puller in the joint gap
- With universal mandrel crimping point below the joint
- Pliers with tether attachment point for mounting a fall protection system
- Solid construction for heaviest strain; universally applicable
- Ergonomically optimised handle shape for firm contact to the hand and fatigue reducing operation
- Particularly effective cross-hatched knurled gripping zone in the jaws for strong gripping and pulling
- Additional gripping zone below the joint for powerful leverage and pressing performance
- With cutting edges for soft and hard wire
- Cutting edges additionally induction-hardened, cutting edge hardness approx. 62 HRC

Cutting capacities medium hard wire (diameter) Ø 4.6 mm

Cutting values hard wire (diameter) Ø 3.0 mm

Length: 240mm

Description

Handles with slim multi-component grips, with integrated tether attachment point for a tool tether.

High transmission ratio for easy cutting

Requires 50 % less effort compared with conventional combination pliers thanks to optimised transmission ratio

With fish tape puller in the joint gap

With universal mandrel crimping point below the joint

Pliers with tether attachment point for mounting a fall protection system

Solid construction for heaviest strain; universally applicable

Ergonomically optimised handle shape for firm contact to the hand and fatigue reducing operation Particularly effective cross-hatched knurled gripping zone in the jaws - for strong gripping and pulling Additional gripping zone below the joint for powerful leverage and pressing performance

With cutting edges for soft and hard wire

Cutting edges additionally induction-hardened, cutting edge hardness approx. 62 HRC Cutting capacities medium hard wire (diameter) Ø 4.6 mm

Cutting values hard wire (diameter) Ø 3.0 mm

Length: 240mm