

# VeEX FX41xT PON-T Power Meter with Visual Fault Locator

Product Images

Product Code: C00-7632



## Short Description

Selective PON Optical Power Meter for G-PON and XGS-PON

1

## 10G Next-Gen and Legacy PON Optical Power Meter

Provides fast, simple, and precise measurement of G-PON and XGS-PON downstream signals. Miniature filters ensure each wavelength is measured accurately. The tester is well suited for installation, service verification, and troubleshooting of co-existent networks, including IEEE based E-PON and 10G-EPON deployments.

Downstream signal verification for 1G/10G PON networks

Simultaneous 1490/1577 nm signal level measurements

Pass/Fail indication per ODN Class or User thresholds

Alkaline or rechargeable NiMH batteries with Auto- off

Save up to 2000 measurements with date and timestamp

Save/display test results via NoApp™ QR code for mobile device transfer, post-processing, sharing, and upload

Cloud-based NoApp™ service (included) allows for data augmentation via mobile phone or tablet.

Secured and always up to date. No installation or updates required.

Micro USB interface for 5V DC powering and battery charging

High contrast backlit, monochrome display - visible outdoors and indoor with varying light conditions

Splash and dust resistant keypad and chassis design

Rugged polycarbonate chassis for demanding field conditions

Fixed SC/APC connector interface with protective dust caps

**Please contact our sales department for further information**

## Description

---

### Selective PON Optical Power Meter for G-PON and XGS-PON

#### 10G Next-Gen and Legacy PON Optical Power Meter

Provides fast, simple, and precise measurement of G-PON and XGS-PON downstream signals. Miniature filters ensure each wavelength is measured accurately. The tester is well suited for installation, service verification, and troubleshooting of co-existent networks, including IEEE based E-PON and 10G-EPON deployments.

Downstream signal verification for 1G/10G PON networks

Simultaneous 1490/1577 nm signal level measurements

Pass/Fail indication per ODN Class or User thresholds

Alkaline or rechargeable NiMH batteries with Auto- off

Save up to 2000 measurements with date and timestamp

Save/display test results via NoApp™ QR code for mobile device transfer, post-processing, sharing, and upload

Cloud-based NoApp™ service (included) allows for data augmentation via mobile phone or tablet.

Secured and always up to date. No installation or updates required.

Micro USB interface for 5V DC powering and battery charging

High contrast backlit, monochrome display - visible outdoors and indoor with varying light conditions

Splash and dust resistant keypad and chassis design

Rugged polycarbonate chassis for demanding field conditions  
Fixed SC/APC connector interface with protective dust caps  
Please contact our sales department for further information