

# VeEX FX45 1310/1550 Optical Light Source OLS

Product Images

Product Code: C00-7631



## Short Description

A low cost, palm-sized single mode optical power meter optimised to suit most broadband networks to

measure and save absolute (dBm) or relative power (dB) levels

The robust VeEx45 is supplied in single mode format with 2 popular wavelengths of 1310/1550 and is ideal for use for PON, Telecom, CATV applications

In addition the OLM is able save over 1000 single results with timestamp which can be transferred and stored to a PC via USB using VeEx Fiberizer Software for report generation

The unit has a splash resistant keypad and chassis design to IP??, as well high contrast display making it visible outdoors and backlight for indoor or low light conditions

Our FX45 is supplied with a SC/APC connector as standard with a number of patch lead adaptors available for use with SC/PC,LC/PC, LC/APC, FC, ST or Optitap

The OPM is supplied with NiMH Battery, AC Adaptor/Power Cord, Carry Pouch

## Description

---

A low cost, palm-sized single mode optical power meter optimised to suit most broadband networks to measure and save absolute (dBm) or relative power (dB) levels

The robust VeEx45 is supplied in single mode format with 2 popular wavelengths of 1310/1550 and is ideal for use for PON, Telecom, CATV applications

In addition the OLM is able save over 1000 single results with timestamp which can be transferred and stored to a PC via USB using VeEx Fiberizer Software for report generation

The unit has a splash resistant keypad and chassis design to IP??, as well high contrast display making it visible outdoors and backlight for indoor or low light conditions

Our FX45 is supplied with a SC/APC connector as standard with a number of patch lead adaptors available for use with SC/PC,LC/PC, LC/APC, FC, ST or Optitap

The OPM is supplied with NiMH Battery, AC Adaptor/Power Cord, Carry Pouch