



Mills Limited  
Unit 2,  
Zodiac Business Park,  
High Road,  
Cowley  
Uxbridge  
UB8 2GU

Contact us on:  
Tel: 020 8833 2626  
Fax: 020 8833 2600  
Email: sales@millsltd.com

Company No. 00282704  
VAT No. 227082574

# Mills Hydraulic Oil 32 - 1 Litre

Product Images

Product Code: S27-1950



## Short Description

---

Mills Hydraulic Oil 32 is a quality anti-wear hydraulic fluid which provides cost effective and reliable protection and performance in most industrial and mobile applications including lubrication of machines and tools moved by compressed air, such as, blowing machines, air compressors and generators.

Pneumatic Oil J32 is expressly formulated for use in hydraulic controls and hydrostatic transmissions, in particular when pressures are high, i.e. on average higher than 70 bar, or the pump operates over 90% of its nominal pressure

### Specification

Density (Kg/L): 0.860

Viscosity (cSt at 40°C): 32

Viscosity (cSt at 100°C): 5.3

VI: 115

Flashpoint (°C): 214

Pour Point (°C): -15

Blended to meet the requirements of the following standards:

DIN 51524 Part 2 (HLP)

Sperry Vickers 1-286-S

ISO 6743/4 (HM)

Afnor NF E 48-603 (HM)

Denison TP 02100

ISO 11158 (HM)

VDMA 24318

US Steel 126,127

Supplied in a 1 litre bottle

## Description

---

Mills Hydraulic Oil 32 is a quality anti-wear hydraulic fluid which provides cost effective and reliable protection and performance in most industrial and mobile applications including lubrication of machines and tools moved by compressed air, such as, blowing machines, air compressors and generators.

Pneumatic Oil J32 is expressly formulated for use in hydraulic controls and hydrostatic transmissions, in particular when pressures are high, i.e. on average higher than 70 bar, or the pump operates over 90% of its nominal pressure

### Specification

2

<https://www.millsltd.com/default/mills-hydraulic-oil-32-1-litre.html>

29/04/2024

Density (Kg/L): 0.860  
Viscosity (cSt at 40°C): 32  
Viscosity (cSt at 100°C): 5.3  
VI: 115  
Flashpoint (°C): 214  
Pour Point (°C): -15

Blended to meet the requirements of the following standards:

DIN 51524 Part 2 (HLP)  
Sperry Vickers 1-286-S  
ISO 6743/4 (HM)  
Afnor NF E 48-603 (HM)  
Denison TP 02100  
ISO 11158 (HM)  
VDMA 24318  
US Steel 126,127

Supplied in a 1 litre bottle