

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Milwaukee M18 18V High Output Li-Ion RedLithium Battery 12.0Ah

Product Images

Product Code: P09-0543



The new M18[™] 12.0 Ah HIGH OUTPUT[™] battery pack provides up to 50% more power vs M18[™] REDLITHIUM[™] battery packs.

Patented REDLINK[™] intelligence protects the pack from tough jobsite conditions to ensure optimum performance.

Runs up to 50% cooler than other M18[™] REDLITHIUM[™] battery packs through heavy applications, allowing professionals to push their cordless tools harder and longer than ever before.

Drives complete corded replacement on the job site with more run time than ever before.

Durable metal frame battery construction with shock responsive separators prevents pack failure from excessive wibrations or drops

vibrations or drops.

On-board battery fuel gauge helps the user to maximise battery run-time efficiency.

Individual cell monitoring ensures optimal charge and discharge for maximum life.

Compatible with all M18[™] tools in the range

Battery pack capacity (Ah) 12.0 Charge time M12_18 AC charger 285 min Charge time M12_18 C charger 250 min Charge time M12_18 FC charger 130 min Charge time M1418C6 charger 270 min Weight (kg) 1.7

Description

The new M18[™] 12.0 Ah HIGH OUTPUT[™] battery pack provides up to 50% more power vs M18[™] REDLITHIUM[™] battery packs.

Patented REDLINK[™] intelligence protects the pack from tough jobsite conditions to ensure optimum performance.

Runs up to 50% cooler than other M18[™] REDLITHIUM[™] battery packs through heavy applications, allowing professionals to push their cordless tools harder and longer than ever before.

Drives complete corded replacement on the job site with more run time than ever before.

Durable metal frame battery construction with shock responsive separators prevents pack failure from excessive

vibrations or drops.

On-board battery fuel gauge helps the user to maximise battery run-time efficiency.

Individual cell monitoring ensures optimal charge and discharge for maximum life.

Compatible with all M18[™] tools in the range

Battery pack capacity (Ah) 12.0 Charge time M12_18 AC charger 285 min Charge time M12_18 C charger 250 min Charge time M12_18 FC charger 130 min Charge time M1418C6 charger 270 min Weight (kg) 1.7