

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600

Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

Martindale PD230SRD Proving Unit

Product Images Product Code: C70-2026









Short Description

Safe electrical working requires the use of a voltage indicator that has been proven with a suitable

proving device before and after use to ensure the instrument is working correctly in accordance with the Electricity at Work Regulations.

The PD230SRD is fast and easy to use, instantly supplying the full test voltage for both high and low impedance voltage indicators, test lamps and meters. It comes complete with an over moulded low-profile case with magnetic hanger.

Description

Safe electrical working requires the use of a voltage indicator that has been proven with a suitable proving device before and after use to ensure the instrument is working correctly in accordance with the Electricity at Work Regulations.

The PD230SRD is fast and easy to use, instantly supplying the full test voltage for both high and low impedance voltage indicators, test lamps and meters. It comes complete with an over moulded low-profile case with magnetic hanger.

Specifications
Output voltage 230V, 120V, 50V nominal
Output frequency DC or 50Hz nominal
Output loading See datasheet
Temperature (Operating & Storage) -10°C to 40°C
Humidity (Operating & Storage) max. 70% R.H.
Altitude up to 2000m
Pollution Degree 2
Power 6 x 1.5V, AA alkaline batteries (IEC LR6, NEDA 15A)
Dimensions 150 x 80 x 35mm
Weight 350g approx. with batteries