

Customer Connection Point With Tray

Product Images

Product Code: CCPA-



Short Description

The CCP (Customer Connection Point) with internal splice management.

Description

The Customer Connection Point (CCP) The closure is manufactured from V0 and UV stable black polycarbonate and has a fully detachable snap on lid. The closure has 2 separate cable access points which are sealed with a silicon cable entry kit (cable diameter range

4.0mm - 6.0mm) to maintain the IP68 rating. A gortex breather membrane is fitted to the lid to prevent condensation forming in the base of the closure. The CCP can also be surface mounted to the wall with an optional sealed rear cable entry/exit point enabling the drop cable to pass directly into the premises.

The unit supports 2 x SC Simplex or 1 x LC Duplex adaptor and provides splice management for 2 x 3A or 2 x ANT splices. Internal fibre management features ensure that a 30mm minimum bend radius is maintained within the closure and provides fibre storage capacity for any excess fibre.

Features & Benefits:

Maximum capacity: 2 x SC Simplex or 1 x LC Duplex Adaptor

Fibre management for 2 x 3A or 2 x ANT splices

Integral positive fibre management and fibre storage capacity

Separate inbound/outbound access points

Cable entry seal 4.0 - 6.0mm

Fully detachable snap on lid

IP68/IK08 Rated

White option available