

Makita 18v Multitool

Product Images

Product Code: P03-0524



Short Description

A handy 18V LXT® multi-function tool for a variety of cutting and polishing applications in construction and renovation projects. Equipped with a tool-less accessory clamp and the oscillating rate can be adjusted between 6 000 and 20 000 min⁻¹.

Description

A handy 18V LXT® multi-function tool for a variety of cutting and polishing applications in construction and renovation projects. Equipped with a tool-less accessory clamp and the oscillating rate can be adjusted between 6 000 and 20 000 min⁻¹.

User benefits

The rubber coating on the handle ensures a firm working grip

Battery protection system automatically shuts off power when the battery level is low

Technical specifications

Nominal Battery Voltage 18 V

Voltage LXT

Orbits per Minute 6000 - 20000 min⁻¹

Oscillation Angle 2 x 1,6 °

Pad size (triangle) 93 x 93 x 93 mm

Sound Pressure Level (LpA) 81 dB(A)

Noise Uncertainty (K Factor) 3 dB(A)

Vibration Level, Sanding 3,0 m/s²

Tool weight with battery 2,0 - 2,4 kg

Product Dimensions (L x W x H): 340 x 80 x 122 mm

Vibration Level, Cutting With Plunge Cut Saw Blade 7,0 m/s²

Vibration Level, Cutting With Segmental Saw Blade 4,5 m/s²

Sound Power Level (LWA) 92 dB(A)

Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) Li-ion

Vibration Level, Scraping 5,5 m/s²

Vibration Uncertainty (K Factor), Cutting With Plunge Cut Saw Blade 1,5 m/s²

Vibration Uncertainty (K Factor), Cutting With Segmental Saw Blade 1,5 m/s²

Vibration Uncertainty (K Factor), Scraping 1,5 m/s²

Vibration Uncertainty (K Factor), Sanding 1,5 m/s²