

Fremco NanoFlow Rapid Kit

Product Images

Product Code:



Short Description

Fibre blowing machine for fibres and micro cables up to 4.5 mm at max 16 bar.

Small but powerful fibre blowing machine, which can blow both blown fibre (EPFU) and micro/nano cables. Tested in accordance to IEC standards.

What's New ?

SAME NANOFLOW, BUT WITH NEW RAPID FEATURES

- Max pressure increased to 16 bar
- Improved safety, the machine has an overpressure valve
- See through lid on the top
- Ball valve connection

Specifications

INCLUDED

- 2 x 24V 2.0 Ah Lithium-ion battery with quick charger
- Filter and water separator
- Rubber drive wheels (2 pcs.)
- Duct adaptor box incl. duct adaptors
- Quality transport box

ADD-ONS

- Adaptor Plate Kit (MANDATORY)
- MAX steel drive wheel for cables from 3.0- 4.5 mm *Item no. 103-190923035*
- Service Agreement with Extended Warranty
- Tripod with quick adaptor *Item No.: 103-161127005*
- Shoulder strap *Item No.: 103-160601074*
- Reel holder arm for pre-connected fibre *Item No.: 103-171020001*

SPECIFICATIONS

Item No.:101-240325001

Cable diameter:.....0.8-4.5 mm

Duct diameter:.....3-12.7 mm

Blowing distance1:.....Up to 1200 m

Blowing speed2:.....Up to 125 m/min

Pushing force:.....0-2 kg

Max. Pressure:.....Max. 16 bar

Recommended airflow3:.....Up to 200 l/pr. min.

Weight:..... 2.9 kg

Length:.....212 mm

Width:.....104 mm

Height:.....139 mm

Description

Fibre blowing machine for fibres and micro cables up to 4.5 mm at max 16 bar

Small but powerful fibre blowing machine, which can blow both blown fibre (EPFU) and micro/nano cables. Tested in accordance to IEC standards.

What's New ?

SAME NANOFLOW, BUT WITH NEW RAPID FEATURES

- Max pressure increased to 16 bar
- Improved safety, the machine has an overpressure valve
- See through lid on the top
- Ball valve connection

Specifications

INCLUDED

- 2 x 24V 2.0 Ah Lithium-ion battery with quick charger
- Filter and water separator
- Rubber drive wheels (2 pcs.)
- Duct adaptor box incl. duct adaptors
- Quality transport box

ADD-ONS

- Adaptor Plate Kit (MANDATORY)
- MAX steel drive wheel for cables from 3.0- 4.5 mm *Item no. 103-190923035*
- Service Agreement with Extended Warranty
- Tripod with quick adaptor - *Item No.: 103-161127005*
- Shoulder strap - *Item No.: 103-160601074*
- Reel holder arm for pre-connected fibre - *Item No.: 103-171020001*

SPECIFICATIONS

Item No.:101-240325001

Cable diameter:.....0.8-4.5 mm

Duct diameter:.....3-12.7 mm

Blowing distance1:.....Up to 1200 m

Blowing speed2:.....Up to 125 m/min

Pushing force:.....0-2 kg

Max. Pressure:.....Max. 16 bar

Recommended airflow3:.....Up to 200 l/pr. min.

Weight:..... 2.9 kg

Length:.....212 mm

Width:.....104 mm

Height:.....139 mm