

Eyebolt Expanding 2A Pk 20

Product Images

Product Code: S83-0901



Short Description

A dropwire fixing consisting of a Zinc plated steel eyebolt with an M10 thread. This is the preferred method of attaching a dropwire to the end users premises, where the walls are rendered.

The eyebolt is suitable for fitting to brick or concrete construction through rendering / pebble-dash upto 20mm thick and has a rated minimum Safe Working Load of 2kN with a safety factor of 3:1 when the load is applied along the axis of the bolt, and at all angles up to 90 degrees to the axis of the bolt.

Zinc coated to Fe/Zn5C2C in accordance with BS 1706

Ring size:14mm

Required Hole size: 16mm diameter x 95mm depth.

Length overall 110mm

These fixings are electric galvanised to (BS1706 (1990) or ISO4520)

Zinc coating: 8 micron minimum

The fixings are expected to provide corrosion resistance for a minimum 25 years
(This cannot be guaranteed and is subject to UK location)

Supplied in a box of 20

Ref: 016442 / 021689 / 023041

Description

A dropwire fixing consisting of a Zinc plated steel eyebolt with an M10 thread. This is the preferred method of attaching a dropwire to the end users premises, where the walls are rendered.

The eyebolt is suitable for fitting to brick or concrete construction through rendering / pebble-dash upto 20mm thick and has a rated minimum Safe Working Load of 2kN with a safety factor of 3:1 when the load is applied along the axis of the bolt, and at all angles up to 90 degrees to the axis of the bolt.

Ring size:14mm

Required Hole size: 16mm diameter x 95mm depth.

These fixings are electric galvanised to (BS1706 (1990) or ISO4520)

Zinc coating: 8 micron minimum

The fixings are expected to provide corrosion resistance for a minimum 25 years
(This cannot be guaranteed and is subject to UK location)

Supplied in a box of 20

Ref: 016442 / 021689 / 023041