

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Fremco MiniFlow Rapid Fibre Blowing Machine

Product Images

Product Code: MINIFLOWRAPID



Short Description

Cable blowing machine for access network.

The Fremco MiniFlow Rapid offers exceptionally rugged construction and high perfomance.

Ensures reliability in all extreme weather conditions, it has been designed to blow fibre cables from 3-12mm into tube sizes 7-20mmm at speeds of up to 100m per minute over distances up to 3.5km.

Rugged stainless construction

The machine is designed based on functionality including:

- Safety chain guard
- Adjustable knobs
- Push force indicator

Fast cable blowing

The machine is capable of installing fibre cable at a speed up to 100 m/min. and up to a distance of 3.5 km making it a compact and efficient cable blowing machine.

Built-in electronic counter and tachometer

The counter is easy to read, robust and simple to operate.

Robust and compact

The machine is constructed in stainless steel and anodized aluminium, which makes it suited for use under

rugged conditions at cable blowing locations.

Flexible

The machine can quickly be adapted to accommodate different cable and duct sizes making it flexible to fit every fibre blowing job

Specifications

Item No.:	101-10031
Cable diameter1:	3-12 mm
Duct diameter:	7-20 mm
Blowing distance2:	Up to 3,500 m
Blowing speed2:	Up to 100 m/min
Pushing force	0-40 kg
Recommended pressure and airflow3:	8-16 bar (1,000 l/pr. min.)
Weight:	24 kg
Length:	650 mm
Width:	225 mm
Height:	210 mm

Description

Cable blowing machine for access network.

The Fremco MiniFlow Rapid offers exceptionally rugged construction and high perfomance.

Ensures reliability in all extreme weather conditions, it has been designed to blow fibre cables from 3-12mm into tube sizes 7-20mmm at speeds of up to 100m per minute over distances up to 3.5km.

Rugged stainless construction

The machine is designed based on functionality including:

- Safety chain guard
- Adjustable knobs
- Push force indicator

Fast cable blowing

The machine is capable of installing fibre cable at a speed up to 100 m/min. and up to a distance of 3.5 km making it a compact and efficient cable blowing machine.

Built-in electronic counter and tachometer

The counter is easy to read, robust and simple to operate.

Robust and compact

The machine is constructed in stainless steel and anodized aluminium, which makes it suited for use under

rugged conditions at cable blowing locations.

Flexible

The machine can quickly be adapted to accommodate different cable and duct sizes making it flexible to fit every fibre blowing job

Specifications

Item No.:	
Cable diameter1:	3-12 mm
Duct diameter:	7-20 mm
Blowing distance2:	Up to 3,500 m
Blowing speed2:	Up to 100 m/min
Pushing force	0-40 kg
Recommended pressure and airflow3:	8-16 bar (1,000 l/pr. min.)
Weight:	24 kg
Length:	650 mm
Width:	225 mm
Height:	210 mm