

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Tempo Compact DSP and PTS Cable Tracer Kit

Product Images

Product Code: C00-8721



A Great Value Package Comprising the Compact DSP Test Set and the PTS Cable Trace Kit The Compact DSP Test Set from Tempo is designed to operate safely in situations where telephone wiring may be carrying digital traffic, voltage feed to remote electronics or the hazardous voltages that result from fault conditions or misuse of the cable.

When set to OFF mode, on connection to a circuit, the test set sounds an alarm to alert the user to the presence of voltages above 75V DC (nominal). These voltages are normally present on circuits carrying digital services. If the circuit is active, the user can select MONITOR mode and listen to the sound to determine if the circuit is carrying digital services without disrupting the traffic.

Selecting TALK mode will stop the alarm signal and loop the line without damage to the test set. If the alarm signal persists, it indicates that the voltage on the line is above 120V (nominal). In this case the line is not looped avoiding damage to the test set as well as alerting the user to the presence of voltages.

- Safe with Data Lines
- Rugged Drop-Proof Design
- Protected against 230 VAC
- Flat Battery always ready feature
- Over Current Protection
- Battery Saving Auto Power-off
- Lightning Surge Protection
- Three-Position Volume Boost
- Finger Tip Microphone Mute
- Headset Socket for Hands Free
- 32-Digit Last Number Redial
- Acoustic Shock Protection
- Supplied complete with cord and BT modular plug

The PTS tone and probe cable trace kit from Tempo is a toner kit designed for identifying and tracing wires or cable within a group without damaging the insulation. Supplied in a sturdy cordura twin-pocket pouch, the kit comprises;

PTS 100 Tone Tracer Probe

- Works with any oscillator 500Hz to 1.2 kHz
- Sensitivity control 30dB adjustment
- Easy push button operation
- Water and dust resistant
- Built in loudspeaker
- Battery life 15-20 hours typ. (1000 traces) IEC61R61

• 210 x 32mm x 42mm, weight 150g (including battery)

PTS 200 Mini Oscillator

• Output level - 3.0dBm

Description

A Great Value Package Comprising the Compact DSP Test Set and the PTS Cable Trace Kit The Compact DSP Test Set from Tempo is designed to operate safely in situations where telephone wiring may be carrying digital traffic, voltage feed to remote electronics or the hazardous voltages that result from fault conditions or misuse of the cable.

When set to OFF mode, on connection to a circuit, the test set sounds an alarm to alert the user to the presence of voltages above 75V DC (nominal). These voltages are normally present on circuits carrying digital services. If the circuit is active, the user can select MONITOR mode and listen to the sound to determine if the circuit is carrying digital services without disrupting the traffic.

Selecting TALK mode will stop the alarm signal and loop the line without damage to the test set. If the alarm signal persists, it indicates that the voltage on the line is above 120V (nominal). In this case the line is not looped avoiding damage to the test set as well as alerting the user to the presence of voltages.

- Safe with Data Lines
- Rugged Drop-Proof Design
- Protected against 230 VAC
- Flat Battery always ready feature
- Over Current Protection
- Battery Saving Auto Power-off
- Lightning Surge Protection
- Three-Position Volume Boost
- Finger Tip Microphone Mute
- Headset Socket for Hands Free
- 32-Digit Last Number Redial
- Acoustic Shock Protection

3

• Supplied complete with cord and BT modular plug

The PTS tone and probe cable trace kit from Tempo is a toner kit designed for identifying and tracing wires or cable within a group without damaging the insulation. Supplied in a sturdy cordura twin-pocket pouch, the kit comprises;

PTS 100 Tone Tracer Probe

- Works with any oscillator 500Hz to 1.2 kHz
- Sensitivity control 30dB adjustment
- Easy push button operation
- Water and dust resistant
- Built in loudspeaker
- Battery life 15-20 hours typ. (1000 traces) IEC61R61
- 210 x 32mm x 42mm, weight 150g (including battery)

PTS 200 Mini Oscillator

• Output level - 3.0dBm