



Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge
UB8 2GU

Contact us on:
Tel: 020 8833 2626
Fax: 020 8833 2600
Email: sales@millsltd.com

Company No. 00282704
VAT No. 227082574

DYMO XTL 12 mm Flexible Cable Wrap Black on White

Product Images

Product Code: C00-6658



Short Description

DYMO XTL labels are durable and made for a variety of surfaces. Whether you are labelling to OSHA, ISO and ANSI colour standards or labelling in harsh conditions, DYMO XTL labels have you covered. Jobsite-

<https://www.millsltd.com/default/dymo-xtl-12-mm-flexible-cable-wrap-black-on-white.html>

28/04/2024

tested and UL-recognised, these labels won't smear or fade. Compatible with DYMO XTL label makers.

- Durable thermal transfer printing technology label text won't smear or fade
- Easy-to-peel split back design and pre-sized labels make applying labels quick and easy

Flexible Cable Wrap.

- For labeling wires, cables and rounded surfaces. Constructed of durable, flexible nylon material designed to conform and stick. Tear-proof material resists damage when pulled through tight spaces or conduits.
- UL recognised as a component to UL 969

This item is suitable for use in the Dymo Rhino XTL-300 and XTL-500 label printers ONLY. Not suitable for any other labellers.

Description

DYMO XTL labels are durable and made for a variety of surfaces. Whether you are labelling to OSHA, ISO and ANSI colour standards or labelling in harsh conditions, DYMO XTL labels have you covered. Jobsite-tested and UL-recognised, these labels won't smear or fade. Compatible with DYMO XTL label makers.

- Durable thermal transfer printing technology label text won't smear or fade
- Easy-to-peel split back design and pre-sized labels make applying labels quick and easy

Flexible Cable Wrap.

- For labeling wires, cables and rounded surfaces. Constructed of durable, flexible nylon material designed to conform and stick. Tear-proof material resists damage when pulled through tight spaces or conduits.
- UL recognised as a component to UL 969

This item is suitable for use in the Dymo Rhino XTL-300 and XTL-500 label printers ONLY. Not suitable for any other labellers.