

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

# **Bollé Bandido Safety Sun Spectacles**

Product Images Product Code: S26-5925



## **Short Description**

Made entirely of highly-resistant polycarbonate, BANDIDO BANPSF is the perfect value safety spectacle option.

Smoke coloured lens and frame.

#### Solar radiations risks: EN 172

Filter protection for industrial solar radiation.

Recommended for outdoor work, EN172 norm guarantee a protection of 99.99% from ultra-violet solar radiation.

Levels of application: 5-3.1 (Polarized) 5-2 (Twilight), 5-1.4 (ESP or CSP), 5/1.1-1.4 (Contrast), 5-2.5 and 5 to 4.1 (smoke)

Lens colour: depends on the lens technology

## Mechanical risk - Low energy impact - F

Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

## Mechanical risk- High speed particles at extreme temperatures - T

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

## **Anti-fog coating**

The anti-fog coating allows you to work in optimal conditions by removing the effect of condensation that occurs when there are large temperature differences or when wearing non-ventilated frames.

#### **Anti-scratch coating**

The anti-scratch coating acts as a shield that improves the resistance of lenses and reduces the formation of scratches. It lengthens the life of the lens and improves user comfort, preventing any scratches that could impair vision.

## **Description**

Made entirely of highly-resistant polycarbonate, BANDIDO BANPSF is the perfect value safety spectacle option.

Smoke coloured lens and frame.

## Solar radiations risks: EN 172

Filter protection for industrial solar radiation.

Recommended for outdoor work, EN172 norm guarantee a protection of 99.99% from ultra-violet solar

Levels of application: 5-3.1 (Polarized) 5-2 (Twilight), 5-1.4 (ESP or CSP), 5/1.1-1.4 (Contrast), 5-2.5 and 5

to 4.1 (smoke)

Lens colour: depends on the lens technology

## Mechanical risk - Low energy impact - F

Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

## Mechanical risk- High speed particles at extreme temperatures - T

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

## **Anti-fog coating**

The anti-fog coating allows you to work in optimal conditions by removing the effect of condensation that occurs when there are large temperature differences or when wearing non-ventilated frames.

## **Anti-scratch coating**

The anti-scratch coating acts as a shield that improves the resistance of lenses and reduces the formation of scratches. It lengthens the life of the lens and improves user comfort, preventing any scratches that could impair vision.