

Lyte NELT325 3 Section Extension Ladder 5.22m EN131-2

Product Images

Product Code: S00-1478





EN131 THE CHANGES EXTENSION LADDERS

BEFORE

- No extra stoppers therefore enabling sections to be separated easily
- 'L' brackets fixed to stile rather than integrated
- No stabilising device incorporated
- Maximum permissible load 150kg
- Standard box section stiles
- Standard rungs

AFTER

- Stoppers added to sections to prevent separation of sections
- Stronger & thicker rungs
- Improved box section stiles and strengthened rungs inline with the new standard requirements.
- Newly designed stabiliser bar which is easy to fit and reduces the risk of sideways slips and gives a larger and safer footprint.
- New improved 'L' brackets for safer use of the sections
- New rung lock to secure the ladder when in use and when stored
- Minimum capacity load of 150kg
- Wider & easier to use
- Tested in the position of use with a load of 270kg

Short Description

Professional 3 section ladder to EN131-2 - 8 rungs per section, 5.22m open, 2.42m closed, weight 17.4kg

Description

Triple section ladder re-designed, tested and manufactured in the UK and built from the best quality aluminium and certified to the new EN131-2 Professional standard for frequent and heavy duty work. Now supplied with a high quality stabiliser bar for maximum safety and stability.

Features

Tested & certified to New EN131-2, Professional

Manufactured with D shaped rung for comfort when climbing.

Newly designed stabiliser bar which is easy to fit and reduces the risk of sideways slips and gives a larger and safer footprint.

Tested to a durability test of 50,000 cycles

Improved box section stiles and strengthened rungs inline with the new standard requirements.

Secure non-slip grip with all round PVC moulded feet

British Made

Specifications

Open Height: 5.22 metres

Closed: 2.42 metres

Number of sections: 3

Rungs per section: 8

Weight: 17.4 kg

Maximum capacity load of 150kg

Due to Health and Safety legislation, all ladders are non-returnable and non-refundable. Once the delivery note has been signed, it will be deemed that the condition of the ladder is new and acceptable.