

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Telesteps Telescopic Combination Ladder 3.0m

Product Images

Product Code: S00-6174





Short Description

A freestanding ladder fully extended for maximum working height, but at a limited height can be used as an A-frame ladder, easily adjusted and used as a leaning ladder. This makes the ladder optimal for those who need a multifunctional ladder for different types of situations.

Ergonomic and safe

Safety on a ladder is the highest priority, that's why Telesteps have a lot of build in safety features. The red tabs are a clear indicator when the rungs are locked and safe to climb. The new 80 mm wide and level rungs with grooved channels give great grip and is very comfortable to stand on for longer periods of time.

The patented triangular tubes make the ladder stronger and more flex resistant thanks to the 2 https://www.millsltd.com/default/telesteps-telescopic-combination-ladder-3-0m.html
02/05/2024 engineering. The shape also makes a perfect grip for your hand when climbing up and down the ladder. Equipped with both rubber tops and feet to avoid slipping.

Flexible and easy to use

The very nature of telescoping ladders makes them easy to transport in almost any vehicle but more importantly easy to carry back and forth the working site even when you need to use an elevator or if there is lack of space.

The newly developed Autolift makes it even easier to carry the Combi Line, especially when moving the ladder during your workday.

In just a couple of seconds you can transform Combi Line from a free-standing ladder into a leaning ladder. Just push the buttons on the back side of the ladder and pull the bottom rungs upwards until you can attach the Easy Lock to the above rung.

Technical Specification

Art. no. 72430-681 Tread width 80 mm Working height 3,8 m Length, closed 0,79 m Width 0,75 m Weight 19,5 kg Max load 150 kg Max users 1

<u>Features</u>

Safe Locking – Red indicator tabs to ensure your safety every time.
Ergonomic – Wide and level rungs to minimize slipping and reduce fatigue.
Safer Rungs – Rungs with grooved channels to disperse dirt.
Integrated Handle – The Combi Line has an integrated handle making it very easy to carry.
Rubber Feet – Maximizing surface contact to avoid slipping.
Rubber Top Section – Works individually on uneven surfaces. Avoids sliding and damaging walls.
Slow Close System – Controlled closing to avoid pinching fingers.
Triangular Design – Twist and flex resistant by nature.
Easy Lock 2 ladders in 1 – Easy to transform from standing ladder to a leaning ladder.
Autolift – Connecting front and back side of the ladder, when lifting.
Smart & Safe Unlocking – Two push buttons on each side for closing the ladder.
Autostep® – Automatic unlocking system when closing the ladder.
EN 131 and SP (RISE) certified

Description

A freestanding ladder fully extended for maximum working height, but at a limited height can be used as an A-frame ladder, easily adjusted and used as a leaning ladder. This makes the ladder optimal for

those who need a multifunctional ladder for different types of situations.

Ergonomic and safe

Safety on a ladder is the highest priority, that's why Telesteps have a lot of build in safety features. The red tabs are a clear indicator when the rungs are locked and safe to climb. The new 80 mm wide and level rungs with grooved channels give great grip and is very comfortable to stand on for longer periods of time.

The patented triangular tubes make the ladder stronger and more flex resistant thanks to the engineering. The shape also makes a perfect grip for your hand when climbing up and down the ladder. Equipped with both rubber tops and feet to avoid slipping.

Flexible and easy to use

The very nature of telescoping ladders makes them easy to transport in almost any vehicle but more importantly easy to carry back and forth the working site even when you need to use an elevator or if there is lack of space.

The newly developed Autolift makes it even easier to carry the Combi Line, especially when moving the ladder during your workday.

In just a couple of seconds you can transform Combi Line from a free-standing ladder into a leaning ladder. Just push the buttons on the back side of the ladder and pull the bottom rungs upwards until you can attach the Easy Lock to the above rung.

Technical Specification

Art. no. 72430-681 Tread width 80 mm Working height 3,8 m Length, closed 0,79 m Width 0,75 m Weight 19,5 kg Max load 150 kg Max users 1

<u>Features</u>

Safe Locking – Red indicator tabs to ensure your safety every time. Ergonomic – Wide and level rungs to minimize slipping and reduce fatigue. Safer Rungs – Rungs with grooved channels to disperse dirt. Integrated Handle – The Combi Line has an integrated handle making it very easy to carry. Rubber Feet – Maximizing surface contact to avoid slipping. Rubber Top Section – Works individually on uneven surfaces. Avoids sliding and damaging walls. Slow Close System – Controlled closing to avoid pinching fingers. Triangular Design – Twist and flex resistant by nature. Easy Lock 2 ladders in 1 – Easy to transform from standing ladder to a leaning ladder. Autolift – Connecting front and back side of the ladder, when lifting. Smart & Safe Unlocking – Two push buttons on each side for closing the ladder. Autostep® – Automatic unlocking system when closing the ladder. Autostep® – Automatic unlocking system when closing the ladder. EN 131 and SP (RISE) certified