


Stainless Steel Ball Lock Cable Tie 362mm x 4.6mm Pk 100

Product Images

Product Code: R02-1975



Short Description

Stainless Steel Ball Lock Cable Tie 362mm x 4.6mm supplied in a pack of 100

304 Grade Stainless Steel Ball-Lock Cable ties are ideal for all applications that require high strength, reliability and fire resistance.

In the event of a fire, cables will remain securely held in place and will not fall to block emergency exits. These MBT (Metal Ball Bearing Ties) ties have a patented non-releasable locking feature and offer infinite adjustment within their length. The MBT ties are heavy duty. Once installed they can be opened and re-used if required.

This range of stainless steel cable ties can be used in chemical industries and on oil platforms as well as in mass transit, shipbuilding and mining industries. MBT ties are also suitable for machine building, apparatus construction and in the outside area of radio technology.

It is strongly recommended that these cable ties are applied using the S00-5631 Tensioning Tool to ensure reliable and efficient fixing.

- Patented non-releasable locking feature
- Corrosion resistant
- Outstanding chemical resistance
- High temperature resistance
- Non-burning

Operating Temperature -80 °C to +538 °C

Bundle Ø max. 102.0mm

Bundle Ø min. 17.0mm

Min.Tensile Strength 900.0N

Length (L) 362.0mm

Thickness (T) 0.3mm

Width (W) 4.6mm

Description

Stainless Steel Ball Lock Cable Tie 362mm x 4.6mm supplied in a pack of 100

304 Grade Stainless Steel Ball-Lock Cable ties are ideal for all applications that require high strength, reliability and fire resistance.

In the event of a fire, cables will remain securely held in place and will not fall to block emergency exits. These MBT (Metal Ball Bearing Ties) ties have a patented non-releasable locking feature and offer infinite adjustment within their length. The MBT ties are heavy duty. Once installed they can be opened and re-used if required.

This range of stainless steel cable ties can be used in chemical industries and on oil platforms as well as in mass transit, shipbuilding and mining industries. MBT ties are also suitable for machine building, apparatus construction and in the outside area of radio technology.

It is strongly recommended that these cable ties are applied using the S00-5631 Tensioning Tool to ensure reliable and efficient fixing.

- Patented non-releasable locking feature
- Corrosion resistant
- Outstanding chemical resistance
- High temperature resistance

- Non-burning

Operating Temperature -80 °C to +538 °C

Bundle Ø max. 102.0mm

Bundle Ø min. 17.0mm

Min.Tensile Strength 900.0N

Length (L) 362.0mm

Thickness (T) 0.3mm

Width (W) 4.6mm