

Bosch 18 Piece HSS-G Toughbox Metal Drill Set 1-10mm

Product Images

Product Code: N36-4736



Short Description

Contains 1, 1.5, 2.5, 3.5, 4.5, 5, 5.5, 6, 7, 8, 9, 10 and 2 x (2, 3 and 4mm).

The HSS Twist Drill Bit Ground is for drilling through metal with maximum precision. The bit's exposed 135-degree self-centring split-point tip combines active cutting and perfect centring without wandering, delivering maximum precision. The split-point tip also eliminates any need to pre-punch or pilot drill for up to 10 mm. This precision-ground bit made of HSS (high-speed steel) enables up to 40% faster drilling rate and up to 50% lower feed pressure than standard-ground HSS drill bits with chisel edges. This bit is designed for drilling holes in alloyed and non-alloyed steel, cast steel, cast iron, sintered iron, malleable cast iron, non-ferrous metals and hard plastics. It has a cylindrical shank system (shank equal to drill bit diameter) and is intended for use in drill stands and drill drivers.

The HSS Twist Drill Bit Ground is manufactured to DIN 338. The drill bit is Type N (flute angle) with a 135-degree tip and a diameter tolerance of h8.

The HSS Twist Drill Bit offers solid drilling for standard usage with metal

135-degree self-centring split-point tip combines active cutting and perfect centring without wandering

Precision-ground bit made of HSS enables fast results No need to pre-punch or pilot drill up to 10 mm-diameter

Bosch Part Number 2607019578

Description

Contains 1, 1.5, 2.5, 3.5, 4.5, 5, 5.5, 6, 7, 8, 9, 10 and 2 x (2, 3 and 4mm).

The HSS Twist Drill Bit Ground is for drilling through metal with maximum precision. The bit's exposed 135-degree self-centring split-point tip combines active cutting and perfect centring without wandering, delivering maximum precision. The split-point tip also eliminates any need to pre-punch or pilot drill for up to 10 mm. This precision-ground bit made of HSS (high-speed steel) enables up to 40% faster drilling rate and up to 50% lower feed pressure than standard-ground HSS drill bits with chisel edges. This bit is designed for drilling holes in alloyed and non-alloyed steel, cast steel, cast iron, sintered iron, malleable cast iron, non-ferrous metals and hard plastics. It has a cylindrical shank system (shank equal to drill bit diameter) and is intended for use in drill stands and drill drivers.

The HSS Twist Drill Bit Ground is manufactured to DIN 338. The drill bit is Type N (flute angle) with a 135-degree tip and a diameter tolerance of h8.

The HSS Twist Drill Bit offers solid drilling for standard usage with metal

135-degree self-centring split-point tip combines active cutting and perfect centring without wandering

Precision-ground bit made of HSS enables fast results No need to pre-punch or pilot drill up to 10 mm-diameter

