

Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Bosch GBH 5-40 DCE 110v SDS Max Rotary Hammer Drill

Product Images Product Code: P09-6875



Short Description

The GBH 5-40 DCE Professional is uniquely designed within Bosch's SDS max corded rotary hammer category for comfortable handling and reduced user fatigue in extensive applications. Its Vibration Control and lightweight design enable effortless and continuous work in time-intensive tasks. The rotary hammer is also built for durability, featuring robust metal components and an optimised lubrication system. Its strong motor enables the delivery of 8.8 J of impact energy for a fast drilling progress and high material removal rate.

This tool is intended for drilling up to 40 mm in diameter and light chiselling work in concrete and stone. It is compatible with various dust attachments.

The GBH 5-40 DCE Professional also features Constant Speed, Rotation Control Clutch, and Speed Selection.

Specification

Rated input power 1,150 W Impact energy 8.8 J Impact rate at rated speed 1,500 – 3,050 bpm Rated speed 170 - 340 rpm Weight 6.8 kg Tool dimensions (length) 485 mm Tool dimensions (height) 260 mm Tool holder SDS max Packaging dimensions (width x length x height) 405 x 610 x 140 mm Voltage, electrical 110 V

Drilling dia. concrete, hammer drill bits 12 – 40 mm

Opt. appl. range concrete, hammer drill bits 18 – 32 mm

Drilling dia. concrete, breakthrough drill bits 45 – 55 mm

Drilling diameter in concrete with core cutters 40 – 90 mm

Description

The GBH 5-40 DCE Professional is uniquely designed within Bosch's SDS max corded rotary hammer category for comfortable handling and reduced user fatigue in extensive applications. Its Vibration Control and lightweight design enable effortless and continuous work in time-intensive tasks. The rotary hammer is also built for durability, featuring robust metal components and an optimised lubrication system. Its strong motor enables the delivery of 8.8 J of impact energy for a fast drilling progress and high material removal rate.

This tool is intended for drilling up to 40 mm in diameter and light chiselling work in concrete and stone. It is compatible with various dust attachments.

The GBH 5-40 DCE Professional also features Constant Speed, Rotation Control Clutch, and Speed

Selection.

Specification

Rated input power 1,150 W Impact energy 8.8 J

Impact rate at rated speed 1,500 – 3,050 bpm

Rated speed 170 - 340 rpm

Weight 6.8 kg

Tool dimensions (length) 485 mm

Tool dimensions (height) 260 mm

Tool holder SDS max

Packaging dimensions (width x length x height) 405 x 610 x 140 mm

Voltage, electrical 110 V

Drilling dia. concrete, hammer drill bits 12 – 40 mm

Opt. appl. range concrete, hammer drill bits 18 – 32 mm

Drilling dia. concrete, breakthrough drill bits 45 – 55 mm

Drilling diameter in concrete with core cutters 40 – 90 mm