

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge UB8 2GU Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

# Bosch GSR 12V-15 FC FlexiClick Cordless Drill Driver Set

**Product Images** 

Product Code: P09-5531



Redefine your limits - the flexibility of five solutions in one compact tool

Versatile: Choice of five options – drill driver with a magnetic bit holder, lockable bit holder, drill chuck, angle adapter and offset angle adapter Compact: Perfect for hard-to-reach places – due to extremely compact design Performing: Convincing power – thanks to 30 Nm of torque

### Performance data

Torque, max. (hard/soft) 30 / 15 Nm No-load speed (1st gear / 2nd gear) 0 – 400 / 0 – 1.300 rpm Battery type Lithium-ion Chuck capacity, min./max. 1 / 10 mm Keyless chuck 10 mm Torque settings 20+1 Bit holder 1/4" internal hexagon

### **Battery and power**

Battery voltage 12 V Cell type Lithium-ion

# Size and Weight

Product Weight excl. battery 0.6 kg Length 132 mm Height 178,0 mm

# **Drilling diameter**

Max. drilling diameter in wood 30 mm Max. drilling diameter in steel 10 mm

# Screw diameter

Max. screw diameter 7 mm

# Contents

- 2 x battery GBA 12 V 2.0 Ah
- Angle adapter GFA 12-W
- Bit holder adapter GFA 12-X
- Drill chuck adapter GFA 12-B
- Offset angle adapter GFA 12-E
- Quick charger GAL 1230 CV
- 1/2 L-BOXX inlay 12 V adapters
- 1/2 L-BOXX inlay for tool and charger

https://www.millsltd.com/default/bosch-gsr-12v-15-fc-flexiclick-cordless-drill-driver-set.html 30/04/2024

• L-BOXX 102

# Description

Redefine your limits - the flexibility of five solutions in one compact tool

Versatile: Choice of five options – drill driver with a magnetic bit holder, lockable bit holder, drill chuck, angle adapter and offset angle adapter Compact: Perfect for hard-to-reach places – due to extremely compact design Performing: Convincing power – thanks to 30 Nm of torque

### Performance data

Torque, max. (hard/soft) 30 / 15 Nm No-load speed (1st gear / 2nd gear) 0 – 400 / 0 – 1.300 rpm Battery type Lithium-ion Chuck capacity, min./max. 1 / 10 mm Keyless chuck 10 mm Torque settings 20+1 Bit holder 1/4" internal hexagon

### **Battery and power**

Battery voltage 12 V Cell type Lithium-ion

# Size and Weight

Product Weight excl. battery 0.6 kg Length 132 mm Height 178,0 mm

# **Drilling diameter**

Max. drilling diameter in wood 30 mm Max. drilling diameter in steel 10 mm

# Screw diameter

Max. screw diameter 7 mm

#### Contents

- 2 x battery GBA 12 V 2.0 Ah
- Angle adapter GFA 12-W
- Bit holder adapter GFA 12-X
- Drill chuck adapter GFA 12-B
- Offset angle adapter GFA 12-E
- Ouick charger GAL 1230 CV

- 1/2 L-BOXX inlay 12 V adapters
- 1/2 L-BOXX inlay for tool and charger
- L-BOXX 102