

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

# Bosch GBH 18 V-26 F SDS Plus Brushless Rotary Hammer

Product Images Product Code: P09-5681



## **Short Description**

Bosch GBH 18 V-26 F SDS+ Plus Brushless Rotary Hammer

- Brushless EC motor: compact, dust-protected, lightweight and absolutely maintenance-free
- Vibration Control: decoupled handle for low user fatigue
- Long runtime: up to 216 holes in concrete with only one battery charge (6 x 40 mm)
- LED worklight: an optimum view of the work position
- Ergonomic design: best horizontal power transfer to the hole
- Electronic Cell Protection (ECP): protects the battery against overloading, overheating and deep discharge
- Innovative COOLPACK batteries: ensure optimum heat dissipation and therefore increase lifetime by up to 100% (cf. Li-Ion batteries without COOLPACK)
- No memory effect: the battery can be charged regardless of the charging state at any time, without damaging the cells
- Fastest charging time: 80% of the battery is charged after 35 mins
- Quick-change chuck for fast changes between drilling with impact in concrete and drilling without impact in wood and metal
- 50% more power with the impact force of a corded tool for fast, versatile use (compared to predecessor GBH 18 V-EC)
- Increased user protection with KickBack Control (KBC) and better control with Electronic Precision Control (EPC)
- Drill without dust thanks to the new integrated, optional GDE 18V-16 dust extraction system

### Performance data

Max. impact energy 2.6 J Impact rate at rated speed 0 – 4.350 bpm Rated speed 0 – 890 rpm Bit holder SDS-plus

## **Battery (Not included)**

Battery voltage 18 V Battery capacity 6,0 Ah

## Size

Length 347,0 mm Height 225,0 mm

## **Drilling range**

Drilling dia. in concrete with hammer drill bits 4 – 26 mm Optimum app. range in concrete with hammer drill bits 8 – 16 mm Max. drilling diameter in steel 13 mm Max. drilling diameter in wood 30 mm

## **Batteries not included**

Supplied with Auxiliary handle, Depth stop, Machine cloth, Quick change chuck 13 mm, SDS plus quick-change chuck in a cardboard box.

## **Description**

Bosch GBH 18 V-26 F SDS+ Plus Brushless Rotary Hammer

- Brushless EC motor: compact, dust-protected, lightweight and absolutely maintenance-free
- Vibration Control: decoupled handle for low user fatigue
- Long runtime: up to 216 holes in concrete with only one battery charge (6 x 40 mm)
- LED worklight: an optimum view of the work position
- Ergonomic design: best horizontal power transfer to the hole
- Electronic Cell Protection (ECP): protects the battery against overloading, overheating and deep discharge
- Innovative COOLPACK batteries: ensure optimum heat dissipation and therefore increase lifetime by up to 100% (cf. Li-Ion batteries without COOLPACK)
- No memory effect: the battery can be charged regardless of the charging state at any time, without damaging the cells
- Fastest charging time: 80% of the battery is charged after 35 mins
- Quick-change chuck for fast changes between drilling with impact in concrete and drilling without impact in wood and metal
- 50% more power with the impact force of a corded tool for fast, versatile use (compared to predecessor GBH 18 V-EC)
- Increased user protection with KickBack Control (KBC) and better control with Electronic Precision Control (EPC)
- Drill without dust thanks to the new integrated, optional GDE 18V-16 dust extraction system

## Performance data

Max. impact energy 2.6 J Impact rate at rated speed 0 – 4.350 bpm Rated speed 0 – 890 rpm Bit holder SDS-plus

## **Battery (Not included)**

Battery voltage 18 V Battery capacity 6,0 Ah

### Size

Length 347,0 mm Height 225,0 mm

## **Drilling range**

Drilling dia. in concrete with hammer drill bits 4 – 26 mm Optimum app. range in concrete with hammer drill bits 8 – 16 mm Max. drilling diameter in steel 13 mm Max. drilling diameter in wood 30 mm

## **Batteries not included**

Supplied with Auxiliary handle, Depth stop, Machine cloth, Quick change chuck 13 mm, SDS plus quick-change chuck in a cardboard box.