

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600

Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

Fusion Cat 6 UTP LS0H Euroclass Dca Cable 305m Blue

Product Images Product Code: T70-6905



Short Description

Fusion 4 Pair UTP Category 6 Euroclass Dca Cable Blue 305m

This CPR (Construction Products Regulation) compliant cable is supplied in reinforced no snag `easy reel' boxes – 305M (1000ft) solid core unshielded cable meeting and exceeds the requirements of TIA/EIA 568A ISO/IEC 11801.

CE marked with a Euroclass Designation as part of the CPR (Construction Products Regulations).

Euroclass reaction to fire: D-s2,d2,a1 (BS EN 13501-6:2014)

- Euroclassification: D-s2,d2,a1 (BS EN 13501-6:2014)
- Fire Behaviour: Dca (BS EN 50399:2011+A1:2016)
- Smoke Production: s2 (BS EN 50399:2011+A1:2016)
- Flaming Droplets: d2 (BS EN 50399:2011+A1:2016)
- Acid Gas Emission/Acidity: a1 (BS EN 60754-2:2014)

Fusion CAT 6 UTP cable meets or exceeds the latest ISO and TIA requirements for category 6 compliance. As with our Cat 5e range, the Fusion CAT 6 product has been designed for ease of use and to save installer time. When installed by a registered Fusion Installer, the system is guaranteed for 25 years.

We've specially designed our Fusion CAT 6 boxes with large cable delivery apertures ensuring a snag free cable delivery. Plastic reinforced handle grips and heavy duty cardboard provide support when carrying boxes on site.

Description

Fusion 4 Pair UTP Category 6 Euroclass Dca Cable Blue 305m

This CPR (Construction Products Regulation) compliant cable is supplied in reinforced no snag `easy reel' boxes – 305M (1000ft) solid core unshielded cable meeting and exceeds the requirements of TIA/EIA 568A ISO/IEC 11801.

CE marked with a Euroclass Designation as part of the CPR (Construction Products Regulations).

Euroclass reaction to fire: D-s2,d2,a1 (BS EN 13501-6:2014)

- Euroclassification: D-s2,d2,a1 (BS EN 13501-6:2014)
- Fire Behaviour: Dca (BS EN 50399:2011+A1:2016)
- Smoke Production: s2 (BS EN 50399:2011+A1:2016)
- Flaming Droplets: d2 (BS EN 50399:2011+A1:2016)
- Acid Gas Emission/Acidity: a1 (BS EN 60754-2:2014)

Fusion CAT 6 UTP cable meets or exceeds the latest ISO and TIA requirements for category 6 compliance. As with our Cat 5e range, the Fusion CAT 6 product has been designed for ease of use and to save installer time. When installed by a registered Fusion Installer, the system is guaranteed for 25 years.

We've specially designed our Fusion CAT 6 boxes with large cable delivery apertures ensuring a snag free cable delivery. Plastic reinforced handle grips and heavy duty cardboard provide support when carrying boxes on site.