

Tempo 500XP Precision Filter Probe

Product Images

Product Code: C00-4599



Short Description

Designed to help technicians install, service, and maintain voice, data, and video (VDV) services with ease, the Tempo 500XP Pair Tracing Probe gets the job done faster, safer, and easier.

Building on the success of the 200XP and 200FP, the 500XP adds new features such as real-time, proportional signal processing and acAlert™ hazardous AC voltage warning.

Other features include a headset connection with improved signal fidelity, and advanced Nautilus® ergonomics and environmental protection, helping you get the job done in even the most demanding conditions.

The Tempo 500XP features a new 32-bit microcontroller, which allows for advanced digital signal processing. With effective filtering, low power consumption, and a rugged weather resistant body, the 500XP lets you trace wires for longer, and with greater accuracy than ever before.

- Two Button Control: Simple, easy to use operation.
- Dual LED Indicators: Provides real-time proportional signal strength feedback.
- acAlert™ Voltage Detection: Emits audible and visible alerts if brought near wires that have AC mains power voltage.
- Mains Hum Filtering: Eliminates hum noise, so you can focus on tracing the correct wire.
- Bandpass Filters: Further reduces noise. Separate LED display with real-time signal strength indicators. Best used when combined with Tempo Tones set to 577 Hz and 983 Hz.
- Industry Standard: Works with a variety of toners (500 Hz to 2.5 kHz).
- Nautilus® Environmental Protection: Environmentally protected against dust and moisture. Drop and Crush resistant.
- Three Year Limited Warranty.

Telephone Compatibility Suitable for telecommunication network (TNV-3) signals. May also be used on other networks with similar maximum voltage limits

Maximum Tip Voltage 100V - Emits audible and visible alerts if brought near 50 - 60 Hz AC power cables (acAlert™)

Maximum Transient 500V (1.2 / 50 µs)

Sensitivity Adjustable, 0 dB to ≥ 60 dB

Frequency Response 200 Hz to 3 kHz

Crush Resistance 2 220 lb (100 kg)

Drop Resistance 3 10 ft (3 m)

Dust Resistance IP67 Rated: Total Dust Ingress Protection

Water Resistance IP67 Rated: Can be submerged in 6" (0.15 m) of water for up to 10 minutes. Floats

Operating Temperature -4 to 122°F (-20 to 50°C)

Hearing Protection < 103 dB SPL Peak when used with Tempo headsets

Battery Type 9V PP3

Battery Life > 50 Hours

Description

Designed to help technicians install, service, and maintain voice, data, and video (VDV) services with ease, the Tempo 500XP Pair Tracing Probe gets the job done faster, safer, and easier.

Building on the success of the 200XP and 200FP, the 500XP adds new features such as real-time, proportional signal processing and acAlert™ hazardous AC voltage warning.

Other features include a headset connection with improved signal fidelity, and advanced Nautilus® ergonomics and environmental protection, helping you get the job done in even the most demanding conditions.

The Tempo 500XP features a new 32-bit microcontroller, which allows for advanced digital signal processing. With effective filtering, low power consumption, and a rugged weather resistant body, the 500XP lets you trace wires for longer, and with greater accuracy than ever before.

- Two Button Control: Simple, easy to use operation.
- Dual LED Indicators: Provides real-time proportional signal strength feedback.
- acAlert™ Voltage Detection: Emits audible and visible alerts if brought near wires that have AC mains power voltage.
- Mains Hum Filtering: Eliminates hum noise, so you can focus on tracing the correct wire.
- Bandpass Filters: Further reduces noise. Separate LED display with real-time signal strength indicators. Best used when combined with Tempo Tones set to 577 Hz and 983 Hz.
- Industry Standard: Works with a variety of toners (500 Hz to 2.5 kHz).
- Nautilus® Environmental Protection: Environmentally protected against dust and moisture. Drop and Crush resistant.
- Three Year Limited Warranty.

Telephone Compatibility Suitable for telecommunication network (TNV-3) signals. May also be used on other networks with similar maximum voltage limits

Maximum Tip Voltage 100V - Emits audible and visible alerts if brought near 50 - 60 Hz AC power cables (acAlert™)

Maximum Transient 500V (1.2 / 50 μ s)

Sensitivity Adjustable, 0 dB to \geq 60 dB

Frequency Response 200 Hz to 3 kHz

Crush Resistance 2 220 lb (100 kg)

Drop Resistance 3 10 ft (3 m)

Dust Resistance IP67 Rated: Total Dust Ingress Protection

Water Resistance IP67 Rated: Can be submerged in 6" (0.15 m) of water for up to 10 minutes. Floats

Operating Temperature -4 to 122°F (-20 to 50°C)

Hearing Protection < 103 dB SPL Peak when used with Tempo headsets

Battery Type 9V PP3

Battery Life > 50 Hours