

Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

RidgeGear RTLE3 Elastic Tool Lanyard with Choke Loop & Belt Attachment 'O' Ring

Product Images Product Code: S00-7567



Short Description

The RTLE3 is an elasticated tool lanyard with a choke loop for tool attachment and an 'O' ring for retention of a tool. It is suitable for tools up to 5kg in weight

The elastic range of lanyards is the next step in tool arrest, allowing the user greater flexibility and usability. These are all made from high quality 20mm elasticated webbing. The benefit of using elasticated webbing is less slack, reducing any trip or snag hazards and keeping all your equipment closer to your body while also offering basic shock absorption.

Length: 0.60 metres (extending to 1.25 metres) Web material: 20mm elasticated polyester

Webbing strength: >1000kg

Tool attachment: 190mm bungee choke loop and 50mm 'O' ring

*Karabiners are shown for illustrative purposes only and are sold separately.

Description

The RTLE3 is an elasticated tool lanyard with a choke loop for tool attachment and an 'O' ring for retention of a tool. It is suitable for tools up to 5kg in weight

The elastic range of lanyards is the next step in tool arrest, allowing the user greater flexibility and usability. These are all made from high quality 20mm elasticated webbing. The benefit of using elasticated webbing is less slack, reducing any trip or snag hazards and keeping all your equipment closer to your body while also offering basic shock absorption.

Length: 0.60 metres (extending to 1.25 metres) Web material: 20mm elasticated polyester

Webbing strength: >1000kg

Tool attachment: 190mm bungee choke loop and 50mm 'O' ring

*Karabiners are shown for illustrative purposes only and are sold separately.