

---

# Mills Fibre Optic Visual Fault Locator 30mW

Product Images

Product Code: C00-5464

---



## Short Description

---

30mW output power VFL offers a dynamic distance of >10km 0 dBm. Includes 2.5mm universal

connector and 1.25mm LC adaptor.

## Key Features

- Slim pen style 650 nm red visible laser diode
- Pulsed (2Hz) and CW operation
- Features a universal connector accepting any optical connector style with 2.5mm ferrule such as FC, SC, ST, E2000 and APC
- Wavelength 650nm 20nm
- 1.25mm adaptor included for LC connectors
- Requires on 2 x AA batteries (not included)
- Dynamic Distance: >10km, 0 dBm
- Size: 180mm(L) \* 30mm(D)
- Weight: 46g

**This a Class 3 laser product and may cause damage if the beam enters the eye directly.**

This generally applies to lasers powered from 5–500 mW. Lasers in this category can cause permanent eye damage with exposures of 1/100th of a second or more depending on the strength of the laser.

## Description

---

30mW output power VFL offers a dynamic distance of >10km 0 dBm. Includes 2.5mm universal connector and 1.25mm LC adaptor.

## Key Features

- Slim pen style 650 nm red visible laser diode
- Pulsed (2Hz) and CW operation
- Features a universal connector accepting any optical connector style with 2.5mm ferrule such as FC, SC, ST, E2000 and APC
- Wavelength 650nm 20nm
- 1.25mm adaptor included for LC connectors
- Requires 2 x AA batteries (not included)
- Dynamic Distance: >10km, 0 dBm
- Size: 180mm(L) \* 30mm(D)
- Weight: 46g

**This a Class 3 laser product and may cause damage if the beam enters the eye directly.**

This generally applies to lasers powered from 5–500 mW. Lasers in this category can cause permanent eye damage with exposures of 1/100th of a second or more depending on the strength of the laser.