

Mills Fibre Optic Visual Fault Locator 30mW

Product Images

Product Code: C00-5464



Short Description

30mW output power VFL offers a dynamic distance of >10km 0 dBm. Includes 2.5mm universal

connector and 1.25mm LC adaptor.

Key Features

- Slim pen style 650 nm red visible laser diode
- Pulsed (2Hz) and CW operation
- Features a universal connector accepting any optical connector style with 2.5mm ferrule such as FC, SC, ST, E2000 and APC
- Wavelength 650nm 20nm
- 1.25mm adaptor included for LC connectors
- Requires on 2 x AA batteries (not included)
- Dynamic Distance: >10km, 0 dBm
- Size: 180mm(L) * 30mm(D)
- Weight: 46g

This a Class 3 laser product and may cause damage if the beam enters the eye directly.

This generally applies to lasers powered from 5–500 mW. Lasers in this category can cause permanent eye damage with exposures of 1/100th of a second or more depending on the strength of the laser.

Description

30mW output power VFL offers a dynamic distance of >10km 0 dBm. Includes 2.5mm universal connector and 1.25mm LC adaptor.

Key Features

- Slim pen style 650 nm red visible laser diode
- Pulsed (2Hz) and CW operation
- Features a universal connector accepting any optical connector style with 2.5mm ferrule such as FC, SC, ST, E2000 and APC
- Wavelength 650nm 20nm
- 1.25mm adaptor included for LC connectors
- Requires 2 x AA batteries (not included)
- Dynamic Distance: >10km, 0 dBm
- Size: 180mm(L) * 30mm(D)
- Weight: 46g

This a Class 3 laser product and may cause damage if the beam enters the eye directly.

This generally applies to lasers powered from 5–500 mW. Lasers in this category can cause permanent eye damage with exposures of 1/100th of a second or more depending on the strength of the laser.