


Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Cat6a Cable Ice Blue U/FTP B2ca 305M

Product Images Product Code: T61-5468



Short Description

This Cat 6A U/FTP Shielded Cable offers independently verified Cat 6A component compliant performance and supports high speed protocols such as 10G Ethernet. The cable is backwards compatible to all preceding cabling categories, ensuring support of all IP applications designed to run over them.

The U/FTP construction does away with the need for a plastic central separator, making the cable more flexible and easier to pull in. The individual foil shielded pairs ensure excellent NEXT performance whilst eliminating the risk of Alien crosstalk and means that a much lower twist rate can be used when compared to a U/UTP or F/UTP construction, thus making termination quicker and easier. The overall diameter of just 7.1mm enables a tighter bend radius (just 28mm after installation) and facilitates the installation of more cables in a given size of containment when compared to cables with an F/UTP construction.

Supplied in 305m box with 305m to 1m cable metre marking making it easy to determine precisely how much cable remains in a box.

Description

This Cat 6A U/FTP Shielded Cable offers independently verified Cat 6A component compliant performance and supports high speed protocols such as 10G Ethernet. The cable is backwards compatible to all preceding cabling categories, ensuring support of all IP applications designed to run over them.

The U/FTP construction does away with the need for a plastic central separator, making the cable more flexible and easier to pull in. The individual foil shielded pairs ensure excellent NEXT performance whilst eliminating the risk of Alien crosstalk and means that a much lower twist rate can be used when compared to a U/UTP or F/UTP construction, thus making termination quicker and easier. The overall diameter of just 7.1mm enables a tighter bend radius (just 28mm after installation) and facilitates the installation of more cables in a given size of containment when compared to cables with an F/UTP construction.

Supplied in 305m box with 305m to 1m cable metre marking making it easy to determine precisely how much cable remains in a box.