

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

BWC25 Barrel Clamp Single Strand Bare Wire 2.5mm

Product Images Product Code: S83-1881



Short Description

For the simple and fast dead-ending of figure-8 cables with steel messengers, comprising a conical body, a pair of wedges, a lanyard and a stainless steel bail.

The clamp body and collar is 70.5 mm by 42 mm. A bail wire is fitted with two ferrules and an insulated UV resistant thermoplastic thimble.

The thimble has a minimum insulating value of 11kV. The bail wire is attached to the collar and held by the two ferrules.

Used for Full Termination of single strand 2.63mm bare catenary wire when replacing existing terminations

Ref 016973

Description

For the simple and fast dead-ending of figure-8 cables with steel messengers, comprising a conical body, a pair of wedges, a lanyard and a stainless steel bail.

The clamp body and collar is 70.5 mm by 42 mm. A bail wire is fitted with two ferrules and an insulated UV resistant thermoplastic thimble.

The thimble has a minimum insulating value of 11kV. The bail wire is attached to the collar and held by the two ferrules.

Used for Full Termination of single strand 2.63mm bare catenary wire when replacing existing terminations

Ref 016973