

CommScope OFDC-A4 External Fibre Optic Splice/Patch Closure

Product Images

Product Code: OFDC-A4



OFDC - A4 - [] / [] - [] - []

Ports	Splitting capacity
<input type="checkbox"/> Adapter panel SC/APC	<input type="checkbox"/> 1:1 (can split 100%)
<input type="checkbox"/> Adapter panel LC/APC	<input type="checkbox"/> 1:2 (can split 50%)
<input type="checkbox"/> Adapter panel SC/UPC	<input type="checkbox"/> 1:2 (can split 50%)
<input type="checkbox"/> Adapter panel LC/UPC	<input type="checkbox"/> 1:2 (can split 50%)
<input type="checkbox"/> SC only	<input type="checkbox"/> No splitting
Number of adapters installed	Mounting kit
<input type="checkbox"/> 4	<input type="checkbox"/> No mounting kit
<input type="checkbox"/> 8 (SC only 4 adapted)	<input type="checkbox"/> 8x 10mm
<input type="checkbox"/> None	<input type="checkbox"/> 1.4 splitter
	Splitter type
	<input type="checkbox"/> 1:2
	<input type="checkbox"/> 1:4
	<input type="checkbox"/> None
	Number of ports installed
	<input type="checkbox"/> 4
	<input type="checkbox"/> 8 (SC only)
	<input type="checkbox"/> None

Short Description

CommScope offers the industry's most versatile Outdoor Fibre Distribution Closure (OFDC) family.

Including three different series, the OFDC family accepts a wide range of distribution and drop cables thus responding to virtually all application requirements.

Each series has a common housing that can be configured to handle different connectivity solutions; such as splice-only, pre-connectorised drop cables, and field-installable connectors (FIC)—significantly simplifying training.

Modularly built, it allows easy integration of optical components, even at later deployment stages, and easy pass-through cabling. Advanced gel sealing technology ensures fast and easy field handling without a need for special tools.

The field friendly design can be installed in pedestal, hand hole, pole or strand mount applications for fast and easy integration into the FTTx network. Strand, Ped and Pole mount bracket accessory kits are also available for easy installation

Features and Benefits

Advanced gel sealing technology ensures fast and easy field handling without a need for special tools
Individual access to drop cable connection area and separate zones for looped cable storage for micro-sheet cables only

Compact and modular design suited for wraparound drop cable installation, enabling faster deployments

Allows easy pass-through cabling and integration of optical components, even at later deployment stages

Characteristics

Main Cable Types

Feeder cables: 2
Round: 4.5-12 mm

Drop Cable Types

Drop cables: 4
Round: 0-6 mm
Flat: 8 x 4.5 mm

Drop cables: 8
Round: 0-4.5 mm

Splice capacity & use (Type: SMOUV 45mm)

24 splices for repair up to 48

Patch capacity

4 SC / 8 LC

Dimensions

Height: 70 mm

Width: 94 mm
Length: 211 mm

Description

CommScope offers the industry's most versatile Outdoor Fiber Distribution Closure (OFDC) family. Including three different series, the OFDC family accepts a wide range of distribution and drop cables thus responding to virtually all application requirements.

Each series has a common housing that can be configured to handle different connectivity solutions; such as splice-only, pre-connectorized drop cables, and field-installable connectors (FIC)—significantly simplifying training.

Modularly built, it allows easy integration of optical components, even at later deployment stages, and easy pass-through cabling. Advanced gel sealing technology ensures fast and easy field handling without a need for special tools.

The field friendly design can be installed in pedestal, hand hole, pole or strand mount applications for fast and easy integration into the FTTx network. Strand, Ped and Pole mount bracket accessory kits are also available for easy installation

Features and Benefits

Advanced gel sealing technology ensures fast and easy field handling without a need for special tools
Individual access to drop cable connection area and separate zones for looped cable storage for micro-sheet cables only

Compact and modular design suited for wraparound drop cable installation, enabling faster deployments

Allows easy pass-through cabling and integration of optical components, even at later deployment stages

Characteristics

Main Cable Types

Feeder cables: 2
Round: 4.5-12 mm

Drop Cable Types

Drop cables: 4
Round: 0-6 mm
Flat: 8 x 4.5 mm

Drop cables: 8
Round: 0-4.5 mm

Splice capacity & use (Type: SMOUV 45mm)

24 splices for repair up to 48

Patch capacity

4 SC / 8 LC

Dimensions

Height: 70 mm

Width: 94 mm

Length: 211 mm

This is a configurable product. Please see ordering guide image and call sales for further details.