

Mills Limited Unit 2, Zodiac Business Park, High Road, Cowley Uxbridge

UB8 2GU

Contact us on: Tel: 020 8833 2626 Fax: 020 8833 2600 Email: sales@millsltd.com Company No. 00282704 VAT No. 227082574

Martindale CM55 AC Clamp Meter

Product Images Product Code: C70-2070









Short Description

The CM55 is a new pocket sized high performance AC Clamp meter measuring AC current, AC/DC voltage and resistance with continuity test. The compact rugged design enables accurate and reliable current measurement down to 10mA resolution without the need to break into the circuit.

Features include a thumbwheel for single handed operation, auto ranging for ease of use, auto powe

off, low battery indicator and a hold function useful for when working in areas with restricted access.

The CM55 is supplied with Martindale TL16 test leads, soft carry case, alkaline batteries and manual. All Martindale clamp meters come with a 2 year warranty.

The CM55 has a CATIII 600V safety rating and is the ideal tool for residential and commercial electricians.

Specifications

Current AC: 40.00A/400.0A (50-400Hz) Accuracy: $\pm 1.9\% \pm 3 \, dgt (50-60 Hz)$ **Voltage AC:** 400.0V/600V (50-400Hz) Accuracy: $\pm 1.2\% \pm 3 \, dgt (50-60 Hz)$

Voltage DC: 400.0V/600V Accuracy: $\pm 1\% \pm 3 \, dgt$

Ohms: 400Ω

Accuracy: $\pm 1\% \pm 2 \, dgt$ Continuity buzzer: $<25\Omega$ Max conductor: 25mmØ

Operating environment: 0°C to 40°C, <80% RH

Supply: 2 x 1.5V AAA Weight: 260g approx

Dimensions: 203 x 75 x 32mm

Includes: TL16 leads, case, batteries and manual

Description

The CM55 is a new pocket sized high performance AC Clamp meter measuring AC current, AC/DC voltage and resistance with continuity test. The compact rugged design enables accurate and reliable current measurement down to 10mA resolution without the need to break into the circuit.

Features include a thumbwheel for single handed operation, auto ranging for ease of use, auto power off, low battery indicator and a hold function useful for when working in areas with restricted access.

The CM55 is supplied with Martindale TL16 test leads, soft carry case, alkaline batteries and manual. All Martindale clamp meters come with a 2 year warranty.

The CM55 has a CATIII 600V safety rating and is the ideal tool for residential and commercial electricians.

Specifications

Current AC: 40.00A/400.0A (50-400Hz) Accuracy: $\pm 1.9\% \pm 3 \, dgt (50-60 Hz)$ **Voltage AC:** 400.0V/600V (50-400Hz)

Voltage DC: 400.0V/600V Accuracy: ± 1% ± 3 dgt

Ohms: 400Ω

Accuracy: \pm 1% \pm 2 dgt **Continuity buzzer:** <25 Ω **Max conductor:** 25mmØ

Operating environment: 0°C to 40°C, <80% RH

Supply: 2 x 1.5V AAA **Weight:** 260g approx

Dimensions: 203 x 75 x 32mm

Includes: TL16 leads, case, batteries and manual