

Mills Limited
Unit 2,
Zodiac Business Park,
High Road,
Cowley
Uxbridge
UB8 2GU

Contact us on: Tel: 020 8833 2626

Fax: 020 8833 2600 Email: sales@millsltd.com

Company No. 00282704 VAT No. 227082574

Martindale HPAT400 Pass/Fail PAT Tester

Product Images Product Code: C70-2072







Short Description

The HPAT400 HandyPAT is an easy to use battery powered, hand-held PAT tester with simple one-button test selection. Its lightweight portable design makes it ideal for testing in all locations whether under a desk or testing a wall mounted monitor.

A single button press activates either a full Class I, Class II or lead test without any further interaction required by the user, unless a failure is encountered.

The display has clear PASS/FAIL indicators but does not display test values. Simple connection diagrams are permanently shown on the case body making it easy to start testing straight away.

The HPAT400 delivery contents include an extension lead adaptor, an earth bond probe

with clip, 6xAA alkaline batteries and a "TEST & GO" carry case with separate pocket for accessories.

Compact portable design with backlit display Easy one button testing Automatic Class I, Class II & power lead tests Clear and simple PASS/FAIL indication IT safe 200mA earth bond test

Specifications

Default pass level Lead: $\geq 1.0 \text{ M}\Omega$ Class I: $\geq 1.0 \text{ M}\Omega$ Class II: $\geq 2.0 \text{ M}\Omega$

Fuse test

Voltage: 4V DC (open circuit)
Current: 200mA DC (short circuit)

Pass level: >2mA

Overload protection 300V AC/DC

Complies with BS EN 61010

Temperature range -10 to 40°C

Supply 6 x 1.2V AA alkaline batteries

Dimensions 90 x 210 x 54mm

Weight 700g (inc batteries & leads)

Includes TC57 carry case, alkaline batteries, EX332 IEC lead, TL67 earth bond probe and manual

Description

The HPAT400 HandyPAT is an easy to use battery powered, hand-held PAT tester with simple one-button test selection. Its lightweight portable design makes it ideal for testing in all locations whether under a desk or testing a wall mounted monitor.

A single button press activates either a full Class I, Class II or lead test without any further interaction required by the user, unless a failure is encountered.

The display has clear PASS/FAIL indicators but does not display test values. Simple connection diagrams are permanently shown on the case body making it easy to start testing straight away.

The HPAT400 delivery contents include an extension lead adaptor, an earth bond probe with clip, 6xAA alkaline batteries and a "TEST & GO" carry case with separate pocket for accessories.

Compact portable design with backlit display Easy one button testing Automatic Class I, Class II & power lead tests

Clear and simple PASS/FAIL indication IT safe 200mA earth bond test

Specifications

Default pass level Lead: $\geq 1.0 \text{ M}\Omega$ Class I: $\geq 1.0 \text{ M}\Omega$ Class II: $\geq 2.0 \text{ M}\Omega$

Fuse test

Voltage: 4V DC (open circuit) Current: 200mA DC (short circuit)

Pass level: >2mA

Overload protection 300V AC/DC

Complies with BS EN 61010

Temperature range -10 to 40°C

Supply 6 x 1.2V AA alkaline batteries

Dimensions 90 x 210 x 54mm

Weight 700g (inc batteries & leads)

Includes TC57 carry case, alkaline batteries, EX332 IEC lead, TL67 earth bond probe and manual