

# Rhino™ 4200











## Compact, Time-Saving Label Maker for On-The-Go Pros

- · Familiar computer-style keyboard with country-specific layout for fast and easy text entry
- One-Touch "Hot Keys" provide shortcuts for creating and formatting wire/cable wraps, flags, Code 39 and Code 128 bar codes, fixed-length, general and breaker labels
- "Favorites" key provides single-key access to your most commonly used labels, symbols and terms
- Avoid repeated steps with the "Custom" key customize and save settings for individual label formats
- Pre-programmed library with 150 symbols and terms for security, electrical, pro A/V, and facilities management
- Integrated rubber bumpers help prevent damage from accidental drops and falls
- · Large back-lit display is easy to read, even in dimly-lit work areas







## Single Unit Includes:

- Rhino 4200 Label Maker
- 12 mm White Vinyl Label Cartridge
- Quick Reference Guide





- AC Adapter
- Carry Case
- Rechargeable Battery





Quick Specs	
Unit Dimensions (H x W x L)	215 x 103 x 57 mm
Weight (excluding battery)	540 g
Mac®/PC Compatible	No
Accepts Label Sizes	6mm, 9mm, 12mm, 19mm
Tape Platform	IND Rhino™
Resolution	180 dpi
Printing System	Thermal Transfer
Print Speed	15mm/sec
Barcodes	Yes, Code 39 & Code 128
Cutter Type	Manual
Batteries	6 AA or Rechargeable (not included)
AC Adapter	Yes (not included)
Networking	No
Country of Origin	China

Item Number	Description		Length (cm)	Width (cm)	Height (cm)	Weight (kg)	QTY	EAN	Customer Price
S0955950	RHINO 4200 QWERTY UK	Unit	8.8	15.6	23.0	0.7	1	3501170955956	
1852992	RHINO 4200 KIT QWERTY UK	Unit	9.2	27.5	26.5	1.1	1	3501178529920	

## Rhino 4200 | Authentic Labels



#### **IND Vinyl**

Ideal for both indoor and outdoor applications. Available in a wide range of colors.

- UL recognized component to UL 969
- · RoHS compliant
- Temperature rating: -40°C to 80°C

## **IND** Flexible Nylon

Specifically designed for curved surfaces and wire and cable marking.

- UL recognized component to UL 969
- · RoHS compliant
- Temperature rating: -10°C to 80°C

### **IND Permanent Polyester**

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins, beams and more.

- UL recognized component to UL 969
- · RoHS compliant
- For flat surfaces only
- Temperature rating: -40°C to 150°C

#### **IND Heat-Shrink Tube**

For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables.

- Meets MIL-M-81531, MIL-STD-202G, SAE-DTL-23053/5 (Class 1 & 3)
- UL recognized as a component to UL 224
- · RoHS compliant
- Temperature rating: -55° C to 135°C

IND Labels										
Width	Length	Α	Α	А	Α	А	Α	Α	А	А
IND VINYL										
9mm	5.5m	18443	-	-	-	-	-	1805437	-	-
12mm		-	-	-	18435	-	1805416	1805435	1805414	1805243
19mm		-	-	18433	-	-	1805422	1805436	1805420	1805417
IND PERMANE	NT POLYESTER									
6mm	5.5m	1805442	1805440	-	-	1805441	-	-	-	-
9mm		18482	18508DM0	-	-	18485	-	-	-	-
12mm		18483	622289	-	-	18486	-	-	-	-
19mm		18484	622290	-	-	18487	-	-	-	-
IND FLEXIBLE	NYLON									
12mm	3.5m	18488	-	18490	-	-	-	-	-	-
19mm	3.5m	18489	-	18491	-	-	-	-	-	-
IND HEAT-SHR	INK TUBE									
6mm	1.5m	18051	-	18052	-	-	-	-	-	-
9mm		18053	-	18054	-	-	-	-	-	-
12mm		18055	-	18056	-	-	-	-	-	-
19mm		18057	-	18058	-	-	-	-	-	-

Country of Origin: Belgium



